




TEST REPORT IEC 62368-1 Audio/video, information and communication technology equipment Part 1: Safety requirements	
Report Number.	AOC250829037S
Date of issue	2025-09-03
Total number of pages	69 pages
Name of Testing Laboratory preparing the Report	Shenzhen AOCE Electronic Technology Service Co., Ltd Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China
Applicant's name	WENZHOU LEGY ELECTRIC METER TECHNOLOGY CO., LTD
Address	ZONE OF INDUSTRY AND TRADE, PANSHI, BEIBAIXIANG TOWN, YUEQING ZHEJIANG, CHINA 325603
Test specification:	
Standard	IEC 62368-1:2018
Test procedure	Test report
Non-standard test method	N/A
TRF template used	IECEE OD-2020-F1:2020, Ed.1.3
Test Report Form No.	IEC 62368_1E
Test Report Form(s) Originator	UL(US)
Master TRF	Dated 2021-02-04
Copyright © 2021 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.	
General disclaimer:	
The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the Testing Laboratory, responsible for this Test Report.	

Test item description	USB SOCKETS	
Trade Mark.....	Zeberg	
Manufacturer	WENZHOU LEGY ELECTRIC METER TECHNOLOGY CO., LTD ZONE OF INDUSTRY AND TRADE, PANSHI, BEIBAIXIANG TOWN, YUEQING ZHEJIANG, CHINA 325603	
Model/Type reference.....	ZBG814	
Ratings.....	For socket part: 250V 16A For switch power supply part: Input: 100-250V~, 50/60Hz, 0.5A Output: USB-A: DC 5V 3A, 9V 2.22A, 12V 1.67A USB-C: DC 5V 3A, 9V 2.22A, 12V 1.67A USB-C+USB-A: DC 5V 3A	
Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):		
☒	Testing Laboratory:	Shenzhen AOCE Electronic Technology Service Co., Ltd
Testing location/ address		Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China
Tested by (name, function, signature)		Bill Hu Technical Engineer 
Approved by (name, function, signature) ..		Robin Liu Technical Manager 
☐	Testing procedure: CTF Stage 1:	
Testing location/ address		
Tested by (name, function, signature)		
Approved by (name, function, signature) ..		
☐	Testing procedure: CTF Stage 2:	
Testing location/ address		
Tested by (name + signature).....		
Witnessed by (name, function, signature) . :		
Approved by (name, function, signature) .. :		
☐	Testing procedure: CTF Stage 3:	
☐	Testing procedure: CTF Stage 4:	
Testing location/ address		
Tested by (name, function, signature)		

Witnessed by (name, function, signature) . :		
Approved by (name, function, signature) .. :		
Supervised by (name, function, signature) :		

List of Attachments (including a total number of pages in each attachment):**Attachment No.1:** Photo document.**Summary of testing:****Tests performed (name of test and test clause):**

- IEC 62368-1:2018


Testing location:

Shenzhen AOCE Electronic Technology Service Co., Ltd
Room 202, 2nd Floor, No.12th Building of Xinhe
Tongfuyu Industrial Park, Fuhai Street, Baoan District,
Shenzhen, Guangdong, China

Summary of compliance with National Differences (List of countries addressed): None
☐ The product fulfils the requirements of.

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.



Notes:

Test item particulars:			
Product group	☐ end product	☒ built-in component	
Classification of use by.....	☐ Ordinary person ☐ Children likely present ☒ Instructed person ☒ Skilled person		
Supply connection.....	☒ AC mains ☐ DC mains ☐ not mains connected: ☐ ES1 ☐ ES2 ☐ ES3		
Supply tolerance	☒ +10%/-10% ☐ +20%/-15% ☐ +____%/ -____% ☐ None		
Supply connection – type	☐ pluggable equipment type A - ☐ non-detachable supply cord ☐ appliance coupler ☐ direct plug-in ☐ pluggable equipment type B - ☐ non-detachable supply cord ☐ appliance coupler ☐ permanent connection ☐ mating connector ☒ other: To be determined on end system		
Considered current rating of protective device	☒ 16A for building; 2A for equipment. Location: ☒ building ☒ equipment ☐ N/A		
Equipment mobility	☐ movable ☐ hand-held ☐ transportable ☐ direct plug-in ☐ stationary ☒ for building-in ☐ wall/ceiling-mounted ☐ SRME/rack-mounted ☐ other:		
Overvoltage category (OVC)	☐ OVC I ☒ OVC II ☐ OVC III ☐ OVC IV		
Class of equipment	☒ Class I ☐ Class II ☐ Class III ☐ Not classified ☐ other:		
Special installation location	☒ N/A ☐ restricted access area ☐ outdoor location ☐ other:		
Pollution degree (PD)	☐ PD 1 ☒ PD 2 ☐ PD 3		
Manufacturer's specified T_{ma}.....	25 °C ☐ Outdoor: minimum ____°C		
IP protection class	☒ IPX0 ☐ IP____		
Power systems	☒ TN ☐ TT ☐ IT - ____ V _{L-L} ☐ not AC mains		
Altitude during operation (m)	☒ 2000 m or less ☐ ____ m		
Altitude of test laboratory (m)	☒ 2000 m or less ☐ ____ m		

Mass of equipment (kg) : Approx. 0.12 kg	
Possible test case verdicts:	
- test case does not apply to the test object.....: N/A	
- test object does meet the requirement.....: P (Pass)	
- test object does not meet the requirement.....: F (Fail)	
Testing:	
Date of receipt of test item : 2025-08-04	
Date (s) of performance of tests : 2025-08-04 to 2025-09-02	
General remarks:	
The tested sample(s) and the sample information are provided by the client. "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Note: EN Group Differences together with National Differences and Special National Conditions, if any, are in the Appendix to the main body of this TRF. Throughout this report a ☐ comma / ☒ point is used as the decimal separator. The test report only allows to be revised only within the report defined retention period unless standard or regulation was withdrawn or invalid. When determining for test conclusion, measurement uncertainty of tests has been considered.	
Manufacturer's Declaration per sub-clause 4.2.5 of IEC 62368-1:	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided:	☐ Yes ☒ Not applicable
When differences exist; they shall be identified in the General product information section.	
Name and address of factory (ies) :	WENZHOU LEGY ELECTRIC METER TECHNOLOGY CO., LTD ZONE OF INDUSTRY AND TRADE, PANSHI, BEIBAIXIANG TOWN, YUEQING ZHEJIANG, CHINA 325603
General product information and other remarks:	
1. This apparatus is USB SOCKETS used for information technology equipment or audio/video equipment. 2. The Clearances and Creepage Distances have additionally been assessed for suitability up to 2000 m. 3. The output ports are in accordance with the PS2. 4. This report only considers the switching power supply part.	

OVERVIEW OF ENERGY SOURCES AND SAFEGUARDS				
Clause	Possible Hazard			
5	Electrically-caused injury			
Class and Energy Source (e.g. ES3: Primary circuit)	Body Part (e.g. Ordinary)	Safeguards		
		B	S	R
ES3: All circuits expect for output circuits	Ordinary	N/A	N/A	Enclosure, see 5.3.2, 5.4.2, 5.4.3, 5.5.3, 5.5.4.
ES1: Output terminals	Ordinary	N/A	N/A	N/A
6	Electrically-caused fire			
Class and Energy Source (e.g. PS2: 100 Watt circuit)	Material part (e.g. Printed board)	Safeguards		
		B	1 st S	2 nd S
PS3	Enclosure	See 6.3	Min.V-0	N/A
PS3	PCB	See 6.3	Min.V-1	N/A
PS3	Internal wiring	See 6.3	See 6.5 (Equipment safeguards, rated VW-1)	N/A
PS3	Other combustible components / materials	See 6.3	See 6.4.5, 6.4.6	N/A
PS2	All combustible material for output terminal	See 6.4	Output terminal material rated V-1 or better	N/A
7	Injury caused by hazardous substances			
Class and Energy Source (e.g. Ozone)	Body Part (e.g., Skilled)	Safeguards		
		B	S	R
N/A	N/A	N/A	N/A	N/A
8	Mechanically-caused injury			
Class and Energy Source (e.g. MS3: Plastic fan blades)	Body Part (e.g. Ordinary)	Safeguards		
		B	S	R
MS1: Equipment Mass	Ordinary	N/A	N/A	N/A
MS1: Sharp edges and corners	Ordinary	N/A	N/A	N/A
9	Thermal burn			
Class and Energy Source (e.g. TS1: Keyboard caps)	Body Part (e.g., Ordinary)	Safeguards		
		B	S	R

TS1: All accessible parts	Ordinary	N/A	N/A	N/A
10	Radiation			
Class and Energy Source (e.g. RS1: PMP sound output)	Body Part (e.g., Ordinary)	Safeguards		
		B	S	R
N/A	N/A	N/A	N/A	N/A
Supplementary Information: “B” – Basic Safeguard; “S” – Supplementary Safeguard; “R” – Reinforced Safeguard				

ENERGY SOURCE DIAGRAM
Optional. Manufacturers are to provide the energy sources diagram identify declared energy sources and identifying the demarcations are between power sources. Recommend diagram be provided included in power supply and multipart systems. Insert diagram below. Example diagram designs are; Block diagrams; image(s) with layered data; mechanical drawings
☒ ES ☒ PS ☒ MS ☒ TS ☐ RS

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
4	GENERAL REQUIREMENTS		P
4.1.1	Acceptance of materials, components and subassemblies	(See appended Table 4.1.2.)	P
4.1.2	Use of components	Components which are certified to IEC and/or national standards are used correctly within their ratings. Components not covered by IEC standards are tested under the conditions present in the equipment. See also Annex G	P
4.1.3	Equipment design and construction	Evaluation of safeguards regarding access to ES3 and to limiting the outputs to fulfill ES1, and protection in regard to risk of spread of fire, mechanical-caused injury and thermal burn considered.	P
4.1.4	Specified ambient temperature for outdoor use (°C):		N/A
4.1.5	Constructions and components not specifically covered		N/A
4.1.8	Liquids and liquid filled components (LFC)		N/A
4.1.15	Markings and instructions	(See Annex F)	P
4.4.3	Safeguard robustness		P
4.4.3.1	General		P
4.4.3.2	Steady force tests	(See Annex T.5)	P
4.4.3.3	Drop tests		N/A
4.4.3.4	Impact tests	(See Annex T.6)	P
4.4.3.5	Internal accessible safeguard tests		N/A
4.4.3.6	Glass impact tests		N/A
4.4.3.7	Glass fixation tests		N/A
	Glass impact test (1J)		N/A
	Push/pull test (10 N)		N/A
4.4.3.8	Thermoplastic material tests	(See Clause T.8)	P
4.4.3.9	Air comprising a safeguard		P
4.4.3.10	Accessibility, glass, safeguard effectiveness	All safeguard remains effective	P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.4.4	Displacement of a safeguard by an insulating liquid		N/A
4.4.5	Safety interlocks		N/A
4.5	Explosion		P
4.5.1	General	No explosion observed during normal / abnormal / single fault conditions.	P
4.5.2	No explosion during normal/abnormal operating condition	(See Clause B.2, B.3)	P
	No harm by explosion during single fault conditions	(See Clause B.4)	P
4.6	Fixing of conductors		P
	Fix conductors not to defeat a safeguard		P
	Compliance is checked by test :	(See Clause T.2)	P
4.7	Equipment for direct insertion into mains socket-outlets		N/A
4.7.2	Mains plug part complies with relevant standard .. :		N/A
4.7.3	Torque (Nm) :		N/A
4.8	Equipment containing coin/button cell batteries		N/A
4.8.1	General		N/A
4.8.2	Instructional safeguard :		N/A
4.8.3	Battery compartment door/cover construction	Not such construction	N/A
	Open torque test		N/A
4.8.4.2	Stress relief test		N/A
4.8.4.3	Battery replacement test		N/A
4.8.4.4	Drop test		N/A
4.8.4.5	Impact test		N/A
4.8.4.6	Crush test		N/A
4.8.5	Compliance		N/A
	30N force test with test probe		N/A
	20N force test with test hook		N/A
4.9	Likelihood of fire or shock due to entry of conductive object		P
4.10	Component requirements		P
4.10.1	Disconnect Device		P
4.10.2	Switches and relays	No such switches and relay used.	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5	ELECTRICALLY-CAUSED INJURY		P
5.2	Classification and limits of electrical energy sources		P
5.2.2	ES1, ES2 and ES3 limits	(See appended table 5.2)	P
5.2.2.2	Steady-state voltage and current limits	(See appended table 5.2)	P
5.2.2.3	Capacitance limits		N/A
5.2.2.4	Single pulse limits.....	No single pulse introduced	N/A
5.2.2.5	Limits for repetitive pulses	No repetitive pulses introduced	N/A
5.2.2.6	Ringing signals	No ringing signals.	N/A
5.2.2.7	Audio signals	No audio signals.	N/A
5.3	Protection against electrical energy sources		P
5.3.1	General Requirements for accessible parts to ordinary, instructed and skilled persons		P
5.3.1 a)	Accessible ES1/ES2 derived from ES2/ES3 circuits		P
5.3.1 b)	Skilled persons not unintentional contact ES3 bare conductors		N/A
5.3.2.1	Accessibility to electrical energy sources and safeguards	Only ES1 parts are accessible by ordinary person.	P
	Accessibility to outdoor equipment bare parts	No outdoor equipment.	N/A
5.3.2.2	Contact requirements		P
	Test with test probe from Annex V	No bare parts at ES2 or ES3 basic safeguard could be accessed by operator.	—
5.3.2.2 a)	Air gap – electric strength test potential (V)		N/A
5.3.2.2 b)	Air gap – distance (mm)	>0.2	P
5.3.2.3	Compliance		P
5.3.2.4	Terminals for connecting stripped wire	No such structure	N/A
5.4	Insulation materials and requirements		P
5.4.1.2	Properties of insulating material		P
5.4.1.3	Material is non-hygroscopic		P
5.4.1.4	Maximum operating temperature for insulating materials	(See appended table 5.4.1.4, 9.3, B.1.5, B.2.6)	P
5.4.1.5	Pollution degrees	PD2	P
5.4.1.5.2	Test for pollution degree 1 environment and for an insulating compound	Pollution degree 2 is applied.	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.4.1.5.3	Thermal cycling test		N/A
5.4.1.6	Insulation in transformers with varying dimensions		N/A
5.4.1.7	Insulation in circuits generating starting pulses		N/A
5.4.1.8	Determination of working voltage	(See appended table 5.4.1.8)	P
5.4.1.9	Insulating surfaces	Considered.	P
5.4.1.10	Thermoplastic parts on which conductive metallic parts are directly mounted		P
5.4.1.10.2	Vicat test		N/A
5.4.1.10.3	Ball pressure test	(See appended table 5.4.1.10.3)	P
5.4.2	Clearances	(see appended table 5.4.2, 5.4.3)	P
5.4.2.1	General requirements		P
	Clearances in circuits connected to AC Mains, Alternative method		P
5.4.2.2	Procedure 1 for determining clearance	(See appended table 5.4.2, 5.4.3)	P
	Temporary overvoltage	2000Vpeak.	—
5.4.2.3	Procedure 2 for determining clearance	(See appended table 5.4.2, 5.4.3)	P
5.4.2.3.2.2	a.c. mains transient voltage	2500Vpeak.	—
5.4.2.3.2.3	d.c. mains transient voltage		—
5.4.2.3.2.4	External circuit transient voltage		—
5.4.2.3.2.5	Transient voltage determined by measurement		—
5.4.2.4	Determining the adequacy of a clearance using an electric strength test	Not such procedure used.	N/A
5.4.2.5	Multiplication factors for clearances and test voltages	Up to 2000m, Factor 1.0	N/A
5.4.2.6	Clearance measurement	(See appended table 5.4.2, 5.4.3)	P
5.4.3	Creepage distances	(See appended table 5.4.2, 5.4.3)	P
5.4.3.1	General	See below.	P
5.4.3.3	Material group	IIIa or IIIb	—

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.4.3.4	Creepage distances measurement	(See appended table 5.4.2, 5.4.3)	P
5.4.4	Solid insulation		P
5.4.4.1	General requirements		P
5.4.4.2	Minimum distance through insulation	(See appended table 5.4.4.2)	P
5.4.4.3	Insulating compound forming solid insulation	Certified source of photo couplers used. (See append table 4.1.2)	P
5.4.4.4	Solid insulation in semiconductor devices	(See clause 5.4.4.3)	P
5.4.4.5	Insulating compound forming cemented joints	No such construction within the EUT	N/A
5.4.4.6	Thin sheet material		P
5.4.4.6.1	General requirements	The thin sheet materials of polyester tape used in transformer.	P
5.4.4.6.2	Separable thin sheet material	Two layers of insulating tape provided as double/reinforced insulation and each layer passed the electric strength test for reinforced insulation. See appended Table 5.4.9.	P
	Number of layers (pcs)	2-layer min.	P
5.4.4.6.3	Non-separable thin sheet material	No non-separable thin sheet material.	N/A
	Number of layers (pcs)		N/A
5.4.4.6.4	Standard test procedure for non-separable thin sheet material		N/A
5.4.4.6.5	Mandrel test		N/A
5.4.4.7	Solid insulation in wound components	See G.5.3 and G.6.1	P
5.4.4.9	Solid insulation at frequencies >30 kHz, E_P , K_R , d , V_{PW} (V)		P
	Alternative by electric strength test, tested voltage (V), K_R	(See appended Tables 5.4.4.9)	P
5.4.5	Antenna terminal insulation	No antenna is used.	N/A
5.4.5.1	General		N/A
5.4.5.2	Voltage surge test		N/A
5.4.5.3	Insulation resistance ($M\Omega$)		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Electric strength test.....:		N/A
5.4.6	Insulation of internal wire as part of supplementary safeguard	No such insulation of internal wire as part of supplementary insulation	N/A
5.4.7	Tests for semiconductor components and for cemented joints		N/A
5.4.8	Humidity conditioning		P
	Relative humidity (%), temperature (°C), duration (h):	95%, 40°C, 120h (Customer requirement)	—
5.4.9	Electric strength test	(See appended table 5.4.9)	P
5.4.9.1	Test procedure for type test of solid insulation.....:	Method 1 used.	P
5.4.9.2	Test procedure for routine test		N/A
5.4.10	Safeguards against transient voltages from external circuits	No such external circuits.	N/A
5.4.10.1	Parts and circuits separated from external circuits		N/A
5.4.10.2	Test methods		N/A
5.4.10.2.1	General		N/A
5.4.10.2.2	Impulse test:		N/A
5.4.10.2.3	Steady-state test.....:		N/A
5.4.10.3	Verification for insulation breakdown for impulse test:		N/A
5.4.11	Separation between external circuits and earth		N/A
5.4.11.1	Exceptions to separation between external circuits and earth	No connection to external circuits with transient voltage.	N/A
5.4.11.2	Requirements		N/A
	SPDs bridge separation between external circuit and earth		N/A
	Rated operating voltage U_{op} (V).....:		—
	Nominal voltage U_{peak} (V).....:		—
	Max increase due to variation ΔU_{sp}:		—
	Max increase due to ageing ΔU_{sa}:		—
5.4.11.3	Test method and compliance:		N/A
5.4.12	Insulating liquid		N/A
5.4.12.1	General requirements		N/A
5.4.12.2	Electric strength of an insulating liquid:		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.4.12.3	Compatibility of an insulating liquid		N/A
5.4.12.4	Container for insulating liquid		N/A
5.5	Components as safeguards		P
5.5.1	General		P
5.5.2	Capacitors and RC units	Approved Y capacitor (See appended table 4.1.2)	P
5.5.2.1	General requirement	Y capacitors complied with clause annex G.11.	P
5.5.2.2	Safeguards against capacitor discharge after disconnection of a connector		N/A
5.5.3	Transformers	(See Annex G.5.3)	P
5.5.4	Optocouplers	(See Annex G.12)	P
5.5.5	Relays	No such relay used as safeguard	N/A
5.5.6	Resistors		N/A
5.5.7	SPDs	No such varistor used	N/A
5.5.8	Insulation between the mains and an external circuit consisting of a coaxial cable		N/A
5.5.9	Safeguards for socket-outlets in outdoor equipment		N/A
	RCD rated residual operating current (mA)		—
5.6	Protective conductor		N/A
5.6.2	Requirement for protective conductors		P
5.6.2.1	General requirements		P
5.6.2.2	Colour of insulation	No switches, current limiting devices or over current protective devices use in Protective conductors.	P
5.6.3	Requirement for protective earthing conductors		N/A
	Protective earthing conductor size (mm ²)	Considered in the terminal equipment	N/A
	Protective earthing conductor serving as a reinforced safeguard		—
	Protective earthing conductor serving as a double safeguard		N/A
5.6.4	Requirements for protective bonding conductors		P
5.6.4.1	Protective bonding conductors		P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Protective bonding conductor size (mm ²)		—
5.6.4.2	Protective current rating (A)	16A	P
5.6.5	Terminals for protective conductors		P
5.6.5.1	Terminal size for connecting protective earthing conductors (mm)	Considered in the terminal equipment	N/A
	Terminal size for connecting protective bonding conductors (mm)		P
5.6.5.2	Corrosion		N/A
5.6.6	Resistance of the protective bonding system		P
5.6.6.1	Requirements		P
5.6.6.2	Test Method	(See appended table 5.6.6)	P
5.6.6.3	Resistance (Ω) or voltage drop	(See appended table 5.6.6)	P
5.6.7	Reliable connection of a protective earthing conductor		N/A
5.6.8	Functional earthing		N/A
	Conductor size (mm ²)		N/A
	Class II with functional earthing marking		N/A
	Appliance inlet cl & cr (mm)		N/A
5.7	Prospective touch voltage, touch current and protective conductor current		P
5.7.2	Measuring devices and networks		P
5.7.2.1	Measurement of touch current	(See appended table 5.7.4)	P
5.7.2.2	Measurement of voltage	(See appended table 5.7.4)	P
5.7.3	Equipment set-up, supply connections and earth connections		P
5.7.4	Unearthed accessible parts	Touch current at unearthed accessible conductive parts is not exceeding ES1 limits. (See appended table 5.7.4)	P
5.7.5	Earthed accessible conductive parts		N/A
5.7.6	Requirements when touch current exceeds ES2 limits		N/A
	Protective conductor current (mA)		N/A
	Instructional Safeguard		N/A
5.7.7	Prospective touch voltage and touch current associated with external circuits		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.7.7.1	Touch current from coaxial cables		N/A
5.7.7.2	Prospective touch voltage and touch current associated with paired conductor cables		N/A
5.7.8	Summation of touch currents from external circuits		N/A
	a) Equipment connected to earthed external circuits, current (mA)..... :		N/A
	b) Equipment connected to unearthed external circuits, current (mA)..... :		N/A
5.8	Backfeed safeguard in battery backed up supplies		N/A
	Mains terminal ES :		N/A
	Air gap (mm)..... :		N/A

6	ELECTRICALLY- CAUSED FIRE		P
6.2	Classification of PS and PIS		P
6.2.2	Power source circuit classifications :	(See appended table 6.2.2)	P
6.2.3	Classification of potential ignition sources	(See appended table 6.2.2)	P
6.2.3.1	Arcing PIS :	(See appended table 6.2.3.1)	P
6.2.3.2	Resistive PIS :	(See appended table 6.2.3.2)	P
6.3	Safeguards against fire under normal operating and abnormal operating conditions		P
6.3.1	No ignition and attainable temperature value less than 90 % defined by ISO 871 or less than 300 °C for unknown materials..... :	(See appended table 5.4.1.4, 9.3, B.1.5, B.2.6)	P
	Combustible materials outside fire enclosure :	V-0	P
6.4	Safeguards against fire under single fault conditions		P
6.4.1	Safeguard method	Method of Control fire spread is used.	P
6.4.2	Reduction of the likelihood of ignition under single fault conditions in PS1 circuits		N/A
6.4.3	Reduction of the likelihood of ignition under single fault conditions in PS2 and PS3 circuits		N/A
6.4.3.1	Supplementary safeguards		N/A
6.4.3.2	Single Fault Conditions..... :		N/A
	Special conditions for temperature limited by fuse		N/A
6.4.4	Control of fire spread in PS1 circuits		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
6.4.5	Control of fire spread in PS2 circuits	See below.	P
6.4.5.2	Supplementary safeguards	All component in PS2 and PS3 is mounted on V-0 Class material of printed boards and comply with the requirements of the relevant IEC components standard, see appended table 4.1.2 and annex G.	P
6.4.6	Control of fire spread in PS3 circuits	All component in PS3 complies with clause (V-0 class material) complies with 6.4.8, see appended table 4.1.2 and annex G.	P
6.4.7	Separation of combustible materials from a PIS	All circuitry and component are considered as PIS. External enclosure material is V-0 class material, see appended table 4.1.2	P
6.4.7.2	Separation by distance	All component and part comply with these requirements.	P
6.4.7.3	Separation by a fire barrier		N/A
6.4.8	Fire enclosures and fire barriers	Equipment enclosure was evaluated as a fire enclosure, internal insulating sheet was evaluated as a fire barrier.	P
6.4.8.2	Fire enclosure and fire barrier material properties	See the following details.	P
6.4.8.2.1	Requirements for a fire barrier		N/A
6.4.8.2.2	Requirements for a fire enclosure	Fire enclosure min. V-0.	P
6.4.8.3	Constructional requirements for a fire enclosure and a fire barrier	Building-in product, to be determined in end system.	N/A
6.4.8.3.1	Fire enclosure and fire barrier openings		N/A
6.4.8.3.2	Fire barrier dimensions		N/A
6.4.8.3.3	Top openings and properties		N/A
	Openings dimensions (mm)..... :		N/A
6.4.8.3.4	Bottom openings and properties		N/A
	Openings dimensions (mm)..... :		N/A
	Flammability tests for the bottom of a fire enclosure		N/A
	Instructional Safeguard:		N/A
6.4.8.3.5	Side openings and properties		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Openings dimensions (mm)..... :		N/A
6.4.8.3.6	Integrity of a fire enclosure, condition met: a), b) or c)..... :	No such door or cover can be opened by ordinary persons.	N/A
6.4.8.4	Separation of a PIS from a fire enclosure and a fire barrier distance (mm) or flammability rating..... :	Fire enclosure min. V-0	P
6.4.9	Flammability of insulating liquid..... :		N/A
6.5	Internal and external wiring		P
6.5.1	General requirements		P
6.5.2	Requirements for interconnection to building wiring..... :		P
6.5.3	Internal wiring size (mm ²) for socket-outlets..... :		N/A
6.6	Safeguards against fire due to the connection to additional equipment		P

7	INJURY CAUSED BY HAZARDOUS SUBSTANCES		N/A
7.2	Reduction of exposure to hazardous substances		N/A
7.3	Ozone exposure		N/A
7.4	Use of personal safeguards or personal protective equipment (PPE)		N/A
	Personal safeguards and instructions..... :		—
7.5	Use of instructional safeguards and instructions		N/A
	Instructional safeguard (ISO 7010)..... :		—
7.6	Batteries and their protection circuits		N/A

8	MECHANICALLY-CAUSED INJURY		P
8.2	Mechanical energy source classifications		P
8.3	Safeguards against mechanical energy sources		P
8.4	Safeguards against parts with sharp edges and corners		P
8.4.1	Safeguards		N/A
	Instructional Safeguard..... :		N/A
8.4.2	Sharp edges or corners	Accessible edges and corners of the equipment are rounded and are classified as MS1.	P
8.5	Safeguards against moving parts		N/A
8.5.1	Fingers, jewellery, clothing, hair, etc., contact with MS2 or MS3 parts		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	MS2 or MS3 part required to be accessible for the function of the equipment		N/A
	Moving MS3 parts only accessible to skilled person		N/A
8.5.2	Instructional safeguard.....:		N/A
8.5.4	Special categories of equipment containing moving parts		N/A
8.5.4.1	General		N/A
8.5.4.2	Equipment containing work cells with MS3 parts		N/A
8.5.4.2.1	Protection of persons in the work cell		N/A
8.5.4.2.2	Access protection override		N/A
8.5.4.2.2.1	Override system		N/A
8.5.4.2.2.2	Visual indicator		N/A
8.5.4.2.3	Emergency stop system		N/A
	Maximum stopping distance from the point of activation (m).....:		N/A
	Space between end point and nearest fixed mechanical part (mm).....:		N/A
8.5.4.2.4	Endurance requirements		N/A
	Mechanical system subjected to 100 000 cycles of operation		N/A
	- Mechanical function check and visual inspection		N/A
	- Cable assembly.....:		N/A
8.5.4.3	Equipment having electromechanical device for destruction of media		N/A
8.5.4.3.1	Equipment safeguards		N/A
8.5.4.3.2	Instructional safeguards against moving parts.....:		N/A
8.5.4.3.3	Disconnection from the supply		N/A
8.5.4.3.4	Cut type and test force (N).....:		N/A
8.5.4.3.5	Compliance		N/A
8.5.5	High pressure lamps		N/A
	Explosion test.....:		N/A
8.5.5.3	Glass particles dimensions (mm).....:		N/A
8.6	Stability of equipment		N/A
8.6.1	General		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Instructional safeguard.....:		N/A
8.6.2	Static stability		N/A
8.6.2.2	Static stability test.....:		N/A
8.6.2.3	Downward force test		N/A
8.6.3	Relocation stability		N/A
	Wheels diameter (mm).....:		—
	Tilt test		N/A
8.6.4	Glass slide test		N/A
8.6.5	Horizontal force test		N/A
8.7	Equipment mounted to wall, ceiling or other structure		N/A
8.7.1	Mount means type.....:		N/A
8.7.2	Test methods		N/A
	Test 1, additional downwards force (N).....:		N/A
	Test 2, number of attachment points and test force (N)		N/A
	Test 3 Nominal diameter (mm) and applied torque (Nm).....:		N/A
8.8	Handles strength		N/A
8.8.1	General		N/A
8.8.2	Handle strength test		N/A
	Number of handles.....:		—
	Force applied (N)		—
8.9	Wheels or casters attachment requirements		N/A
8.9.2	Pull test		N/A
8.10	Carts, stands and similar carriers		N/A
8.10.1	General		N/A
8.10.2	Marking and instructions		N/A
8.10.3	Cart, stand or carrier loading test		N/A
	Loading force applied (N).....:		N/A
8.10.4	Cart, stand or carrier impact test		N/A
8.10.5	Mechanical stability		N/A
	Force applied (N)		—

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
8.10.6	Thermoplastic temperature stability		N/A
8.11	Mounting means for slide-rail mounted equipment (SRME)		N/A
8.11.1	General		N/A
8.11.2	Requirements for slide rails		N/A
	Instructional Safeguard		N/A
8.11.3	Mechanical strength test		N/A
8.11.3.1	Downward force test, force (N) applied		N/A
8.11.3.2	Lateral push force test		N/A
8.11.3.3	Integrity of slide rail end stops		N/A
8.11.4	Compliance		N/A
8.12	Telescoping or rod antennas		N/A
	Button/ball diameter (mm)		—
9	THERMAL BURN INJURY		P
9.2	Thermal energy source classifications		P
9.3	Touch temperature limits		P
9.3.1	Touch temperatures of accessible parts	All accessible surfaces are classified as TS1 (See appended table 5.4.1.4, 9.3, B.1.5, B.2.6)	P
9.3.2	Test method and compliance	(See appended table 5.4.1.4, 9.3, B.1.5, B.2.6)	P
9.4	Safeguards against thermal energy sources		P
9.5	Requirements for safeguards		P
9.5.1	Equipment safeguard		P
9.5.2	Instructional safeguard		N/A
9.6	Requirements for wireless power transmitters		N/A
9.6.1	General		N/A
9.6.2	Specification of the foreign objects		N/A
9.6.3	Test method and compliance	(See appended table 9.6)	N/A
10	RADIATION		N/A
10.2	Radiation energy source classification		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
10.2.1	General classification		N/A
	Lasers		—
	Lamps and lamp systems		—
	Image projectors		—
	X-Ray		—
	Personal music player		—
10.3	Safeguards against laser radiation		N/A
	The standard(s) equipment containing laser(s) comply		N/A
10.4	Safeguards against optical radiation from lamps and lamp systems (including LED types)		N/A
10.4.1	General requirements		N/A
	Instructional safeguard provided for accessible radiation level needs to exceed		N/A
	Risk group marking and location		N/A
	Information for safe operation and installation		N/A
10.4.2	Requirements for enclosures		N/A
	UV radiation exposure		N/A
10.4.3	Instructional safeguard		N/A
10.5	Safeguards against X-radiation		N/A
10.5.1	Requirements		N/A
	Instructional safeguard for skilled persons		—
10.5.3	Maximum radiation (pA/kg).....		—
10.6	Safeguards against acoustic energy sources		N/A
10.6.1	General		N/A
10.6.2	Classification		N/A
	Acoustic output $L_{Aeq,T}$, dB(A)		N/A
	Unweighted RMS output voltage (mV)		N/A
	Digital output signal (dBFS)		N/A
10.6.3	Requirements for dose-based systems		N/A
10.6.3.1	General requirements		N/A
10.6.3.2	Dose-based warning and automatic decrease		N/A
10.6.3.3	Exposure-based warning and requirements		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	30 s integrated exposure level (MEL30)		N/A
	Warning for MEL ≥ 100 dB(A)		N/A
10.6.4	Measurement methods		N/A
10.6.5	Protection of persons		N/A
	Instructional safeguards..... :	State in user manual	N/A
10.6.6	Requirements for listening devices (headphones, earphones, etc.)		N/A
10.6.6.1	Corded listening devices with analogue input		N/A
	Listening device input voltage (mV)..... :		N/A
10.6.6.2	Corded listening devices with digital input		N/A
	Max. acoustic output $L_{Aeq,T}$, dB(A)		N/A
10.6.6.3	Cordless listening devices		N/A
	Max. acoustic output $L_{Aeq,T}$, dB(A)		N/A

B	NORMAL OPERATING CONDITION TESTS, ABNORMAL OPERATING CONDITION TESTS AND SINGLE FAULT CONDITION TESTS		P
B.1	General		P
B.1.5	Temperature measurement conditions	(See appended table 5.4.1.4, 9.3, B.1.5, B.2.6)	P
B.2	Normal operating conditions		P
B.2.1	General requirements	(See Test Item Particulars and appended test tables)	P
	Audio Amplifiers and equipment with audio amplifiers		N/A
B.2.3	Supply voltage and tolerances	+10% and -10% for a.c. mains.	P
B.2.5	Input test	(See appended table B.2.5)	P
B.3	Simulated abnormal operating conditions		P
B.3.1	General	(See appended tables B.3, B.4)	P
B.3.2	Covering of ventilation openings	Building-in equipment shall be evaluated in end system.	N/A
	Instructional safeguard		N/A
B.3.3	DC mains polarity test	The equipment is not connected to a D.C. mains.	N/A
B.3.4	Setting of voltage selector	No voltage selector	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
B.3.5	Maximum load at output terminals	(See appended tables B.3, B.4)	P
B.3.6	Reverse battery polarity	No batteries	N/A
B.3.7	Audio amplifier abnormal operating conditions	No audio amplifier	N/A
B.3.8	Safeguards functional during and after abnormal operating conditions..... :	All safeguards remained effective. (See appended tables B.3, B.4)	P
B.4	Simulated single fault conditions		P
B.4.1	General		P
B.4.2	Temperature controlling device	No temperature controlling device	N/A
B.4.3	Blocked motor test	No motors	N/A
B.4.4	Functional insulation	(See appended tables B.3, B.4)	P
B.4.4.1	Short circuit of clearances for functional insulation	(See appended tables B.3, B.4)	P
B.4.4.2	Short circuit of creepage distances for functional insulation	(See appended tables B.3, B.4)	P
B.4.4.3	Short circuit of functional insulation on coated printed boards	No coated printed boards	N/A
B.4.5	Short-circuit and interruption of electrodes in tubes and semiconductors	(See appended tables B.3, B.4)	P
B.4.6	Short circuit or disconnection of passive components	(See appended tables B.3, B.4)	P
B.4.7	Continuous operation of components	The equipment is continuous operating type and no such components intended for short time operation or intermittent operation.	N/A
B.4.8	Compliance during and after single fault conditions :	(See appended tables B.3, B.4)	P
B.4.9	Battery charging and discharging under single fault conditions		N/A
C	UV RADIATION		N/A
C.1	Protection of materials in equipment from UV radiation		N/A
C.1.2	Requirements		N/A
C.1.3	Test method		N/A
C.2	UV light conditioning test		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
C.2.1	Test apparatus..... :		N/A
C.2.2	Mounting of test samples		N/A
C.2.3	Carbon-arc light-exposure test		N/A
C.2.4	Xenon-arc light-exposure test		N/A
D	TEST GENERATORS		N/A
D.1	Impulse test generators		N/A
D.2	Antenna interface test generator		N/A
D.3	Electronic pulse generator		N/A
E	TEST CONDITIONS FOR EQUIPMENT CONTAINING AUDIO AMPLIFIERS		N/A
E.1	Electrical energy source classification for audio signals		N/A
	Maximum non-clipped output power (W)..... :		—
	Rated load impedance (Ω) :		—
	Open-circuit output voltage (V) :		—
	Instructional safeguard :		—
E.2	Audio amplifier normal operating conditions		N/A
	Audio signal source type..... :		—
	Audio output power (W) :		—
	Audio output voltage (V) :		—
	Rated load impedance (Ω) :		—
	Requirements for temperature measurement		N/A
E.3	Audio amplifier abnormal operating conditions	(See appended table 5.4.1.4, 9.3, B.1.5, B.2.6)	N/A
F	EQUIPMENT MARKINGS, INSTRUCTIONS, AND INSTRUCTIONAL SAFEGUARDS		P
F.1	General		P
	Language :	English. Versions in other languages will be provided when national certificate approval.	—
F.2	Letter symbols and graphical symbols		P
F.2.1	Letter symbols according to IEC60027-1	Letter symbols for quantities and units are complied with IEC 60027-1.	P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
F.2.2	Graphic symbols according to IEC, ISO or manufacturer specific	Graphical symbols are complied with IEC 60417, ISO 3864-2, ISO 7000 or ISO 7010.	P
F.3	Equipment markings		P
F.3.1	Equipment marking locations	The equipment marking is located on the surface and is easily visible.	P
F.3.2	Equipment identification markings	See below.	P
F.3.2.1	Manufacturer identification	See copy of marking plate	P
F.3.2.2	Model identification	See copy of marking plate	P
F.3.3	Equipment rating markings	See copy of marking plate	P
F.3.3.1	Equipment with direct connection to mains	See copy of marking plate	P
F.3.3.2	Equipment without direct connection to mains		N/A
F.3.3.3	Nature of the supply voltage	See copy of marking plate	P
F.3.3.4	Rated voltage.....	See copy of marking plate	P
F.3.3.5	Rated frequency	See copy of marking plate	P
F.3.3.6	Rated current or rated power.....	See copy of marking plate	P
F.3.3.7	Equipment with multiple supply connections	Only one connection.	N/A
F.3.4	Voltage setting device	No voltage setting device.	N/A
F.3.5	Terminals and operating devices	See below.	P
F.3.5.1	Mains appliance outlet and socket-outlet markings		N/A
F.3.5.2	Switch position identification marking.....		N/A
F.3.5.3	Replacement fuse identification and rating markings	The Fuse is located within the equipment and not replaceable by an ordinary person or an instructed person. The fuse marking is marked on PCB near fuse: F1 T2A/ 250V	P
	Instructional safeguards for neutral fuse		N/A
F.3.5.4	Replacement battery identification marking.....		N/A
F.3.5.5	Neutral conductor terminal		N/A
F.3.5.6	Terminal marking location		N/A
F.3.6	Equipment markings related to equipment classification		P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
F.3.6.1	Class I equipment	See below.	P
F.3.6.1.1	Protective earthing conductor terminal		N/A
F.3.6.1.2	Protective bonding conductor terminals		P
F.3.6.2	Equipment class marking.....	See copy of marking plate.	P
F.3.6.3	Functional earthing terminal marking		N/A
F.3.7	Equipment IP rating marking	IPX0	N/A
F.3.8	External power supply output marking		N/A
F.3.9	Durability, legibility and permanence of marking	All markings required are easily discernible under normal lighting conditions.	P
F.3.10	Test for permanence of markings	After rubbing test by water and petroleum spirit, the marking still legible; it is not easily possible to remove the marking plate and show no curling.	P
F.4	Instructions		P
	a)..... Information prior to installation and initial use	Relevant safety caution texts and installation instruction are available	P
	b)..... Equipment for use in locations where children not likely to be present		N/A
	c)..... Instructions for installation and interconnection	Relevant safety caution texts and installation instruction are available.	P
	d)..... Equipment intended for use only in restricted access area		N/A
	e)..... Equipment intended to be fastened in place		N/A
	f)..... Instructions for audio equipment terminals		N/A
	g)..... Protective earthing used as a safeguard		N/A
	h)..... Protective conductor current exceeding ES2 limits		N/A
	a)..... Graphic symbols used on equipment		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	b)..... Permanently connected equipment not provided with all-pole mains switch		N/A
	c)..... Replaceable components or modules providing safeguard function		N/A
	d)..... Equipment containing insulating liquid		N/A
	e)..... Installation instructions for outdoor equipment		N/A
F.5	Instructional safeguards		N/A
G	COMPONENTS		P
G.1	Switches		N/A
G.1.1	General	No switches	N/A
G.1.2	Ratings, endurance, spacing, maximum load		N/A
G.1.3	Test method and compliance		N/A
G.2	Relays		N/A
G.2.1	Requirements		N/A
G.2.2	Overload test		N/A
G.2.3	Relay controlling connectors supplying power to other equipment		N/A
G.2.4	Test method and compliance		N/A
G.3	Protective devices		N/A
G.3.1	Thermal cut-offs		N/A
	Thermal cut-outs separately approved according to IEC 60730 with conditions indicated in a) & b)		N/A
	Thermal cut-outs tested as part of the equipment as indicated in c)		N/A
G.3.1.2	Test method and compliance		N/A
G.3.2	Thermal links		N/A
G.3.2.1	a) Thermal links tested separately according to IEC 60691 with specifics		N/A
	b) Thermal links tested as part of the equipment		N/A
G.3.2.2	Test method and compliance		N/A
G.3.3	PTC thermistors		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.3.4	Overcurrent protection devices	Approved fuse is used (See appended table 4.1.2)	P
G.3.5	Safeguards components not mentioned in G.3.1 to G.3.4		N/A
G.3.5.1	Non-resettable devices suitably rated and marking provided		N/A
G.3.5.2	Single faults conditions		N/A
G.4	Connectors		N/A
G.4.1	Spacings		N/A
G.4.2	Mains connector configuration.....		N/A
G.4.3	Plug is shaped that insertion into mains socket-outlets or appliance coupler is unlikely		N/A
G.5	Wound components		P
G.5.1	Wire insulation in wound components	Approved TIW used for secondary winding of T1	P
G.5.1.2	Protection against mechanical stress	Physical separation is provided (by insulating tube)	P
G.5.2	Endurance test		N/A
G.5.2.1	General test requirements		N/A
G.5.2.2	Heat run test		N/A
	Test time (days per cycle).....		—
	Test temperature (°C)		—
G.5.2.3	Wound components supplied from the mains		N/A
G.5.2.4	No insulation breakdown		N/A
G.5.3	Transformers	See below.	P
G.5.3.1	Compliance method	The transformers meet the requirements given in G.5.3.2 and G.5.3.3.	P
	Position	T1	P
	Method of protection	Over current protection by circuit design.	P
G.5.3.2	Insulation	Primary windings and secondary windings are separated by Reinforced insulation.	P
	Protection from displacement of windings	By bobbin and insulating tape	—

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.5.3.3	Transformer overload tests	(See appended tables B.3, B.4)	P
G.5.3.3.1	Test conditions	Tested in the complete equipment.	P
G.5.3.3.2	Winding temperatures	(See appended table B.3, B.4)	P
G.5.3.3.3	Winding temperatures - alternative test method		N/A
G.5.3.4	Transformers using FIW		N/A
G.5.3.4.1	General		N/A
	FIW wire nominal diameter :		—
G.5.3.4.2	Transformers with basic insulation only		N/A
G.5.3.4.3	Transformers with double insulation or reinforced insulation :		N/A
G.5.3.4.4	Transformers with FIW wound on metal or ferrite core		N/A
G.5.3.4.5	Thermal cycling test and compliance		N/A
G.5.3.4.6	Partial discharge test		N/A
G.5.3.4.7	Routine test		N/A
G.5.4	Motors		N/A
G.5.4.1	General requirements		N/A
G.5.4.2	Motor overload test conditions		N/A
G.5.4.3	Running overload test		N/A
G.5.4.4.2	Locked-rotor overload test		N/A
	Test duration (days) :		—
G.5.4.5	Running overload test for DC motors		N/A
G.5.4.5.2	Tested in the unit		N/A
G.5.4.5.3	Alternative method		N/A
G.5.4.6	Locked-rotor overload test for DC motors		N/A
G.5.4.6.2	Tested in the unit		N/A
	Maximum Temperature :		N/A
G.5.4.6.3	Alternative method		N/A
G.5.4.7	Motors with capacitors		N/A
G.5.4.8	Three-phase motors		N/A
G.5.4.9	Series motors		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Operating voltage		—
G.6	Wire Insulation		P
G.6.1	General	Approved triple insulated wires comply with Annex J.	P
G.6.2	Enamelled winding wire insulation	Solvent-based enamel winding is not considered basic insulation.	N/A
G.7	Mains supply cords		N/A
G.7.1	General requirements		N/A
	Type		—
G.7.2	Cross sectional area (mm ² or AWG)		N/A
G.7.3	Cord anchorages and strain relief for non-detachable power supply cords		N/A
G.7.3.2	Cord strain relief		N/A
G.7.3.2.1	Requirements		N/A
	Strain relief test force (N)		N/A
G.7.3.2.2	Strain relief mechanism failure		N/A
G.7.3.2.3	Cord sheath or jacket position, distance (mm)		N/A
G.7.3.2.4	Strain relief and cord anchorage material		N/A
G.7.4	Cord Entry		N/A
G.7.5	Non-detachable cord bend protection		N/A
G.7.5.1	Requirements		N/A
G.7.5.2	Test method and compliance		N/A
	Overall diameter or minor overall dimension, <i>D</i> (mm)		—
	Radius of curvature after test (mm)		—
G.7.6	Supply wiring space		N/A
G.7.6.1	General requirements		N/A
G.7.6.2	Stranded wire		N/A
G.7.6.2.1	Requirements		N/A
G.7.6.2.2	Test with 8 mm strand		N/A
G.8	Varistors		N/A
G.8.1	General requirements		N/A
G.8.2	Safeguards against fire		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.8.2.1	General		N/A
G.8.2.2	Varistor overload test		N/A
G.8.2.3	Temporary overvoltage test		N/A
G.9	Integrated circuit (IC) current limiters		N/A
G.9.1	Requirements		N/A
	IC limiter output current (max. 5A)..... :		—
	Manufacturers' defined drift :		—
G.9.2	Test Program		N/A
G.9.3	Compliance		N/A
G.10	Resistors		N/A
G.10.1	General		N/A
G.10.2	Conditioning		N/A
G.10.3	Resistor test		N/A
G.10.4	Voltage surge test		N/A
G.10.5	Impulse test		N/A
G.10.6	Overload test		N/A
G.11	Capacitors and RC units		P
G.11.1	General requirements	The Y-Capacitor (CY1) are used as safeguard and complied with IEC/EN 60384-14:2013 (See appended table 4.1.2).	P
G.11.2	Conditioning of capacitors and RC units		P
G.11.3	Rules for selecting capacitors		P
G.12	Optocouplers		P
	Optocouplers comply with IEC 60747-5-5 with specifics	The optocouplers (U2) used in the equipment are complied with IEC/EN 60747-5-5. (See appended table 4.1.2)	P
	Type test voltage $V_{ini,a}$:		—
	Routine test voltage, $V_{ini,b}$:		—
G.13	Printed boards		P
G.13.1	General requirements		P
G.13.2	Uncoated printed boards		P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.13.3	Coated printed boards		N/A
G.13.4	Insulation between conductors on the same inner surface		N/A
G.13.5	Insulation between conductors on different surfaces		N/A
	Distance through insulation :		N/A
	Number of insulation layers (pcs) :		—
G.13.6	Tests on coated printed boards		N/A
G.13.6.1	Sample preparation and preliminary inspection		N/A
G.13.6.2	Test method and compliance		N/A
G.14	Coating on components terminals		N/A
G.14.1	Requirements :	(See Clause G.13)	N/A
G.15	Pressurized liquid filled components		N/A
G.15.1	Requirements		N/A
G.15.2	Test methods and compliance		N/A
G.15.2.1	Hydrostatic pressure test		N/A
G.15.2.2	Creep resistance test		N/A
G.15.2.3	Tubing and fittings compatibility test		N/A
G.15.2.4	Vibration test		N/A
G.15.2.5	Thermal cycling test		N/A
G.15.2.6	Force test		N/A
G.15.3	Compliance		N/A
G.16	IC including capacitor discharge function (ICX)		N/A
G.16.1	Condition for fault tested is not required		N/A
	ICX with associated circuitry tested in equipment		N/A
	ICX tested separately		N/A
G.16.2	Tests		N/A
	Smallest capacitance and smallest resistance specified by ICX manufacturer for impulse test..... :		—
	Mains voltage that impulses to be superimposed on :		—
	Largest capacitance and smallest resistance for ICX tested by itself for 10000 cycles test..... :		—
G.16.3	Capacitor discharge test..... :		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
H	CRITERIA FOR TELEPHONE RINGING SIGNALS		N/A
H.1	General		N/A
H.2	Method A		N/A
H.3	Method B		N/A
H.3.1	Ringling signal		N/A
H.3.1.1	Frequency (Hz)		—
H.3.1.2	Voltage (V)		—
H.3.1.3	Cadence; time (s) and voltage (V)		—
H.3.1.4	Single fault current (mA):		—
H.3.2	Tripping device and monitoring voltage		N/A
H.3.2.1	Conditions for use of a tripping device or a monitoring voltage		N/A
H.3.2.2	Tripping device		N/A
H.3.2.3	Monitoring voltage (V).....		N/A
J	INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION		P
J.1	General		P
	Winding wire insulation	Approved triple insulated wire used. (See appended table 4.1.2)	—
	Solid round winding wire, diameter (mm)		N/A
	Solid square and rectangular (flatwise bending) winding wire, cross-sectional area (mm ²).....		N/A
J.2/J.3	Tests and Manufacturing	(See separate test report)	—
K	SAFETY INTERLOCKS		N/A
K.1	General requirements		N/A
	Instructional safeguard		N/A
K.2	Components of safety interlock safeguard mechanism		N/A
K.3	Inadvertent change of operating mode		N/A
K.4	Interlock safeguard override		N/A
K.5	Fail-safe		N/A
K.5.1	Under single fault condition		N/A
K.6	Mechanically operated safety interlocks		N/A
K.6.1	Endurance requirement		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
K.6.2	Test method and compliance		N/A
K.7	Interlock circuit isolation		N/A
K.7.1	Separation distance for contact gaps & interlock circuit elements		N/A
	In circuit connected to mains, separation distance for contact gaps (mm)		N/A
	In circuit isolated from mains, separation distance for contact gaps (mm)		N/A
	Electric strength test before and after the test of K.7.2.....		N/A
K.7.2	Overload test, Current (A).....		N/A
K.7.3	Endurance test		N/A
K.7.4	Electric strength test		N/A
L	DISCONNECT DEVICES		N/A
L.1	General requirements		N/A
L.2	Permanently connected equipment		N/A
L.3	Parts that remain energized		N/A
L.4	Single-phase equipment		N/A
L.5	Three-phase equipment		N/A
L.6	Switches as disconnect devices		N/A
L.7	Plugs as disconnect devices		N/A
L.8	Multiple power sources		N/A
	Instructional safeguard		N/A
M	EQUIPMENT CONTAINING BATTERIES AND THEIR PROTECTION CIRCUITS		N/A
M.1	General requirements		N/A
M.2	Safety of batteries and their cells		N/A
M.2.1	Batteries and their cells comply with relevant IEC standards		N/A
M.3	Protection circuits for batteries provided within the equipment		N/A
M.3.1	Requirements		N/A
M.3.2	Test method		N/A
	Overcharging of a rechargeable battery		N/A
	Excessive discharging		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Unintentional charging of a non-rechargeable battery		N/A
	Reverse charging of a rechargeable battery		N/A
M.3.3	Compliance		N/A
M.4	Additional safeguards for equipment containing a portable secondary lithium battery		N/A
M.4.1	General		N/A
M.4.2	Charging safeguards		N/A
M.4.2.1	Requirements		N/A
M.4.2.2	Compliance		N/A
M.4.3	Fire enclosure		N/A
M.4.4	Drop test of equipment containing a secondary lithium battery		N/A
M.4.4.2	Preparation and procedure for the drop test		N/A
M.4.4.3	Drop, Voltage on reference and dropped batteries (V); voltage difference during 24 h period (%):		N/A
M.4.4.4	Check of the charge/discharge function		N/A
M.4.4.5	Charge / discharge cycle test		N/A
M.4.4.6	Compliance		N/A
M.5	Risk of burn due to short-circuit during carrying		N/A
M.5.1	Requirement		N/A
M.5.2	Test method and compliance		N/A
M.6	Safeguards against short-circuits		N/A
M.6.1	External and internal faults		N/A
M.6.2	Compliance		N/A
M.7	Risk of explosion from lead acid and NiCd batteries		N/A
M.7.1	Ventilation preventing explosive gas concentration		N/A
	Calculated hydrogen generation rate		N/A
M.7.2	Test method and compliance		N/A
	Minimum air flow rate, Q (m ³ /h)		N/A
M.7.3	Ventilation tests		N/A
M.7.3.1	General		N/A
M.7.3.2	Ventilation test – alternative 1		N/A
	Hydrogen gas concentration (%)		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
M.7.3.3	Ventilation test – alternative 2		N/A
	Obtained hydrogen generation rate		N/A
M.7.3.4	Ventilation test – alternative 3		N/A
	Hydrogen gas concentration (%)		N/A
M.7.4	Marking		N/A
M.8	Protection against internal ignition from external spark sources of batteries with aqueous electrolyte		N/A
M.8.1	General		N/A
M.8.2	Test method		N/A
M.8.2.1	General		N/A
M.8.2.2	Estimation of hypothetical volume V_z (m ³ /s).....		—
M.8.2.3	Correction factors		—
M.8.2.4	Calculation of distance d (mm)		—
M.9	Preventing electrolyte spillage		N/A
M.9.1	Protection from electrolyte spillage		N/A
M.9.2	Tray for preventing electrolyte spillage		N/A
M.10	Instructions to prevent reasonably foreseeable misuse		N/A
	Instructional safeguard		N/A
N	ELECTROCHEMICAL POTENTIALS		N/A
	Material(s) used		—
O	MEASUREMENT OF CREEPAGE DISTANCES AND CLEARANCES		P
	Value of X (mm).....	Measurement is in accordance with applicable figures.	—
P	SAFEGUARDS AGAINST CONDUCTIVE OBJECTS		N/A
P.1	General		N/A
P.2	Safeguards against entry or consequences of entry of a foreign object		N/A
P.2.1	General		N/A
P.2.2	Safeguards against entry of a foreign object		N/A
	Location and Dimensions (mm)		—
P.2.3	Safeguards against the consequences of entry of a foreign object		N/A
P.2.3.1	Safeguard requirements		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	The ES3 and PS3 keep-out volume in Figure P.3 not applicable to transportable equipment		N/A
	Transportable equipment with metalized plastic parts		N/A
P.2.3.2	Consequence of entry test.....		N/A
P.3	Safeguards against spillage of internal liquids		N/A
P.3.1	General		N/A
P.3.2	Determination of spillage consequences		N/A
P.3.3	Spillage safeguards		N/A
P.3.4	Compliance		N/A
P.4	Metallized coatings and adhesives securing parts		N/A
P.4.1	General		N/A
P.4.2	Tests		N/A
	Conditioning, T _c (°C)		—
	Duration (weeks).....		—
Q	CIRCUITS INTENDED FOR INTERCONNECTION WITH BUILDING WIRING		P
Q.1	Limited power sources		P
Q.1.1	Requirements		P
	a) Inherently limited output		N/A
	b) Impedance limited output		N/A
	c) Regulating network limited output	(See appended table Q.1)	P
	d) Overcurrent protective device limited output		N/A
	e) IC current limiter complying with G.9		N/A
Q.1.2	Test method and compliance	(See appended table Q.1)	P
	Current rating of overcurrent protective device (A)		N/A
Q.2	Test for external circuits – paired conductor cable		N/A
	Maximum output current (A)		N/A
	Current limiting method.....		—
R	LIMITED SHORT CIRCUIT TEST		N/A
R.1	General		N/A
R.2	Test setup		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Overcurrent protective device for test..... :		—
R.3	Test method		N/A
	Cord/cable used for test..... :		—
R.4	Compliance		N/A
S	TESTS FOR RESISTANCE TO HEAT AND FIRE		N/A
S.1	Flammability test for fire enclosures and fire barrier materials of equipment where the steady state power does not exceed 4 000 W		N/A
	Samples, material :		—
	Wall thickness (mm) :		—
	Conditioning (°C) :		—
	Test flame according to IEC 60695-11-5 with conditions as set out		N/A
	- Material not consumed completely		N/A
	- Material extinguishes within 30s		N/A
	- No burning of layer or wrapping tissue		N/A
S.2	Flammability test for fire enclosure and fire barrier integrity		N/A
	Samples, material :		—
	Wall thickness (mm) :		—
	Conditioning (°C) :		—
S.3	Flammability test for the bottom of a fire enclosure		N/A
S.3.1	Mounting of samples		N/A
S.3.2	Test method and compliance		N/A
	Mounting of samples :		—
	Wall thickness (mm) :		—
S.4	Flammability classification of materials		N/A
S.5	Flammability test for fire enclosures and fire barrier materials of equipment where the steady state power exceeding 4 000 W		N/A
	Samples, material :		—
	Wall thickness (mm) :		—
	Conditioning (°C) :		—
T	MECHANICAL STRENGTH TESTS		P
T.1	General		P
T.2	Steady force test, 10 N :	(See appended table T.2)	P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
T.3	Steady force test, 30 N :		N/A
T.4	Steady force test, 100 N :		N/A
T.5	Steady force test, 250 N :	(See appended table T.5)	P
T.6	Enclosure impact test	(See appended table T.6)	P
	Fall test		P
	Swing test		P
T.7	Drop test :		N/A
T.8	Stress relief test..... :	(See appended table T.8)	P
T.9	Glass Impact Test :		N/A
T.10	Glass fragmentation test		N/A
	Number of particles counted.....:		N/A
T.11	Test for telescoping or rod antennas		N/A
	Torque value (Nm)		N/A
U	MECHANICAL STRENGTH OF CATHODE RAY TUBES (CRT) AND PROTECTION AGAINST THE EFFECTS OF IMPLOSION		N/A
U.1	General		N/A
	Instructional safeguard :		N/A
U.2	Test method and compliance for non-intrinsically protected CRTs		N/A
U.3	Protective screen		N/A
V	DETERMINATION OF ACCESSIBLE PARTS		P
V.1	Accessible parts of equipment		P
V.1.1	General	Following the probes test specified in this annex Figure V.1, V.2, V.3 are suitable.	P
V.1.2	Surfaces and openings tested with jointed test probes		P
V.1.3	Openings tested with straight unjointed test probes		N/A
V.1.4	Plugs, jacks, connectors tested with blunt probe		P
V.1.5	Slot openings tested with wedge probe		N/A
V.1.6	Terminals tested with rigid test wire		P
V.2	Accessible part criterion		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
X	ALTERNATIVE METHOD FOR DETERMINING CLEARANCES FOR INSULATION IN CIRCUITS CONNECTED TO AN AC MAINS NOT EXCEEDING 420 V PEAK (300 V RMS)		N/A
	Clearance :	(See appended table X)	N/A
Y	CONSTRUCTION REQUIREMENTS FOR OUTDOOR ENCLOSURES		N/A
Y.1	General		N/A
Y.2	Resistance to UV radiation		N/A
Y.3	Resistance to corrosion		N/A
Y.3	Resistance to corrosion		N/A
Y.3.1	Metallic parts of outdoor enclosures are resistant to effects of water-borne contaminants by..... :		N/A
Y.3.2	Test apparatus		N/A
Y.3.3	Water – saturated sulphur dioxide atmosphere		N/A
Y.3.4	Test procedure :		N/A
Y.3.5	Compliance		N/A
Y.4	Gaskets		N/A
Y.4.1	General		N/A
Y.4.2	Gasket tests		N/A
Y.4.3	Tensile strength and elongation tests		N/A
	Alternative test methods :		N/A
Y.4.4	Compression test		N/A
Y.4.5	Oil resistance		N/A
Y.4.6	Securing means		N/A
Y.5	Protection of equipment within an outdoor enclosure		N/A
Y.5.1	General		N/A
Y.5.2	Protection from moisture		N/A
	Relevant tests of IEC 60529 or Y.5.3 :		N/A
Y.5.3	Water spray test		N/A
Y.5.4	Protection from plants and vermin		N/A
Y.5.5	Protection from excessive dust		N/A
Y.5.5.1	General		N/A
Y.5.5.2	IP5X equipment		N/A
Y.5.5.3	IP6X equipment		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
Y.6	Mechanical strength of enclosures		N/A
Y.6.1	General		N/A
Y.6.2	Impact test :		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict

5.2	TABLE: Classification of electrical energy sources						P
Supply Voltage	Location (e.g. circuit designation)	Test conditions	Parameters				ES Class
			U (V)	I (mA)	Type ¹⁾	Additional Info ²⁾	
275Vac	Primary circuits supplied by a.c. mains supply	Normal	--	--	--	--	ES3 (declared)
		Abnormal – see table B.3, B.4 for detail	--	--	--	--	
		Single fault – see table B.3, B.4 for detail	--	--	--	--	
275Vac	Plastic enclosure to earth	Normal	--	0.154m Apk	SS	--	ES1
		Abnormal – see table B.3, B.4 for detail	--	0.154m Apk	SS	--	ES1
		Single fault – see table B.3, B.4 for detail	--	0.154m Apk	SS	--	ES1
275Vac	USB-C Output “+” to “-”	Normal	Max. 12.15Vdc	--	SS	--	ES1
		Abnormal – see table B.3, B.4 for detail	Max. 12.15Vdc	--	SS	--	ES1
		Single fault – see table B.3, B.4 for detail	Max. 12.15Vdc	--	SS	--	ES1
275Vac	USB-A Output “+” to “-”	Normal	Max.12.03Vdc	--	SS	--	ES1
		Abnormal – see table B.3, B.4 for detail	Max.12.03Vdc	--	SS	--	ES1
		Single fault – see table B.3, B.4 for detail	Max.12.03Vdc	--	SS	--	ES1
275Vac	Output terminal “+/-” to GND	Normal	--	0.325m Apk	SS	--	ES1

IEC 62368-1							
Clause	Requirement + Test				Result - Remark		Verdict
		Abnormal – see table B.3, B.4 for detail	--	0.325m Apk	SS	--	ES1
		Single fault – see table B.3, B.4 for detail	--	0.325m Apk	SS	--	ES1
Supplementary information:							
1) Type: Steady state (SS), Capacitance (CP), Single pulse (SP), Repetitive pulses (RP), etc.							
2) Additional Info: Frequency, Pulse duration, Pulse off time, Capacitance value, etc.							

5.4.1.8	TABLE: Working voltage measurement				P
Location	RMS voltage (V)	Peak voltage (V)	Frequency (Hz)	Comments	
T1 Pin 7-A	266	526	37.82K	Max. VPeak voltage Max. VRMS voltage	
T1 Pin 8-A	251	501	37.82K	--	
T1 Pin 4-A	227	487	37.82K	--	
T1 Pin 3-A	214	469	37.82K	--	
T1 Pin 7-B	266	524	37.82K	--	
T1 Pin 8-B	247	498	37.82K	--	
T1 Pin 3-B	226	484	37.82K	--	
T1 Pin 4-B	212	466	37.82K	--	
U2 Pin 3-1	232	363	60	--	
U2 Pin 4-1	231	363	60	--	
U2 Pin 3-2	229	363	60	--	
U2 Pin 4-2	229	361	60	--	
CY1 Primary pin to secondary pin	222	353	60	--	
Supplementary information: 240Vac, 60Hz; Load: UBS-C DC 12V 1.67A					

5.4.1.10.2	TABLE: Vicat softening temperature of thermoplastics			N/A
Method			ISO 306 / B50	—
Object/ Part No./Material	Manufacturer/trademark	Thickness (mm)	T softening (°C)	
--	--	--	--	
Supplementary information: N/A				

IEC 62368-1				
Clause	Requirement + Test		Result - Remark	Verdict
5.4.1.10.3	TABLE: Ball pressure test of thermoplastics			P
Allowed impression diameter (mm)..... :			≤ 2 mm	—
Object/Part No./Material	Manufacturer/trademark	Thickness (mm)	Test temperature (°C)	Impression diameter (mm)
Enclosure	SABIC INNOVATIVE PLASTICS US L L C	2.0	125	1.15
Supplementary information: N/A				

5.4.2, 5.4.3	TABLE: Minimum Clearances/Creepage distance							P
Clearance (cl) and creepage distance (cr) at/of/between:	U _p (V)	U _{rms} (V)	Freq ¹⁾ (Hz)	Required cl (mm)	cl (mm)	E.S. ²⁾ (V)	Required cr (mm)	cr (mm)
Basic / supplementary:								
Different polarity of L/N before fuse F1	<420	<250	60	1.5	5.1	--	2.5	5.1
Different polarity of fuse F1	<420	<250	60	1.5	3.3	--	2.5	3.3
L to G	<420	<250	60	1.5	4.2	--	2.5	4.2
N to G	<420	<250	60	1.5	4.2	--	2.5	4.2
Reinforced:								
Primary trace to secondary trace under U2	<420	<250	60	3.0	7.1	--	5.0	7.1
Primary trace to secondary trace under CY1	<420	<250	60	3.0	7.1	--	5.0	7.1
Primary circuit to accessible enclosure	<420	<250	60	3.0	7.5	--	5.0	7.5
Primary component and secondary component	526	266	37.82k	3.0	7.1	--	6.0	7.1
Primary component and secondary winding	526	266	37.82k	3.0	6.2	--	6.0	6.2
Primary component to secondary component (USB terminal)	526	266	37.82k	3.0	7.1	--	6.0	7.1

IEC 62368-1								
Clause	Requirement + Test				Result - Remark			Verdict
Core of T1 to secondary component	526	266	37.82k	3.0	8.2	--	6.0	8.2
Primary winding to secondary winding of T1	526	266	37.82k	3.0	8.2	--	6.0	8.2
Supplementary information: 1) Only for frequency above 30 kHz 2) Complete Electric Strength voltage (E.S. (V) when 5.4.2.4 applied) 3) For clearance and creepage did not describe above are far larger than limit above. The secondary of T1 used triple insulated wire, core as primary of T1.								

5.4.4.2	TABLE: Minimum distance through insulation				P
Distance through insulation (DTI) at/of	Peak voltage (V)	Insulation	Required DTI (mm)	Measured DTI (mm)	
Bobbin of T1	526Vac	Reinforce	0.4	Min. 0.7	
Plastic enclosure	526Vac	Reinforce	0.4	Min. 1.5	
Insulation tape	526Vac	Reinforce	2 layers	Min. 2 layers	
Supplementary information: N/A					

5.4.4.9	TABLE: Solid insulation at frequencies >30 kHz						P
Insulation material	E_P	Frequency (kHz)	K_R	Thickness d (mm)	Insulation	V_{PW} (Vpk)	
T1 bobbin (phenolic)	17	37.82	0.71	Min. 0.7	Reinforce	526	
2 layers insulation tape used on T1 (polyethylene)	52	37.82	0.46	Min. 2 layers	Reinforce	526	
Supplementary information: N/A							

5.4.9	TABLE: Electric strength tests			P
Test voltage applied between:		Voltage shape (Surge, Impulse, AC, DC, etc.)	Test voltage (V)	Breakdown Yes / No
Basic/supplementary				
L to N (with F1 opened)		DC	2500VDC	No
L/N to G		DC	2500VDC	No
Reinforced:				

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
L/N to output terminal	DC	4000VDC	No
L/N to plastic enclosure wrapped with metal foil	DC	4000VDC	No
Primary to secondary of transformer T1	DC	4000VDC	No
Secondary to core of transformer T1	DC	4000VDC	No
Insulation tape used in and around transformer T1 (single layer)	DC	4000VDC	No
From Enclosure inside to Enclosure outside	DC	4000VDC	No
Supplementary information: N/A			

5.5.2.2	TABLE: Stored discharge on capacitors					N/A
Location	Supply voltage (V)	Operating and fault condition ¹⁾	Switch position	Measured voltage (Vpk)	ES Class	
--	--	--	--	--	--	
Supplementary information: X-capacitors installed for testing: ☐ bleeding resistor rating: ☐ ICX: 1) Normal operating condition (e.g., normal operation, or open fuse), SC= short circuit, OC= open circuit						

5.6.6	TABLE: Resistance of protective conductors and terminations				P
Location		Test current (A)	Duration (min)	Voltage drop (V)	Resistance (Ω)
GND pin of AC Inlet to farthest metal end		32	2	--	0.009
Supplementary information: N/A					

5.7.4	TABLE: Unearthed accessible parts					P
Location	Operating and fault conditions	Supply Voltage (V)	Parameters			ES class
			Voltage (V _{rms} or V _{pk})	Current (A _{rms} or A _{pk})	Freq. (Hz)	
USB-C Output terminals	Normal	275Vac	Max.12.15Vdc	--	60	ES1
	Abnormal – see table B.3, B.4 for detail	275Vac	Max.12.15Vdc	--	60	ES1
	Single fault – see table B.3, B.4 for	275Vac	Max.12.15Vdc	--	60	ES1

IEC 62368-1						
Clause	Requirement + Test		Result - Remark			Verdict
	detail					
USB-A Output terminals	Normal	275Vac	Max.12.03Vdc	--	60	ES1
	Abnormal – see table B.3, B.4 for detail	275Vac	Max.12.03Vdc	--	60	ES1
	Single fault – see table B.3, B.4 for detail	275Vac	Max.12.03Vdc	--	60	ES1
Plastic enclosure with metal foil	Normal	275Vac	--	0.154mA _{pk}	60	ES1
	Abnormal – see table B.3, B.4 for detail	275Vac	--	0.154mA _{pk}	60	ES1
	Single fault – see table B.3, B.4 for detail	275Vac	--	0.154mA _{pk}	60	ES1
Supplementary information: Abbreviation: SC= short circuit; OC= open circuit						

5.7.5	TABLE: Earthed accessible conductive part				N/A
Supply voltage (V) :		--			—
Phase(s) :		[] Single Phase; [] Three Phase: [] Delta [] Wye			—
Power Distribution System :		☐ TN ☐ TT ☐ IT			—
Location		Fault Condition No in IEC 60990 clause 6.2.2	Touch current (mA)	Comment	
--		--	--	--	
Supplementary Information: N/A					

5.8	TABLE: Backfeed safeguard in battery backed up supplies					N/A
Location	Supply voltage (V)	Operating and fault condition	Time (s)	Open-circuit voltage (V)	Touch current (A)	ES Class
--	--	--	--	--	--	--
Supplementary information: Abbreviation: SC= short circuit, OC= open circuit						

6.2.2	TABLE: Power source circuit classifications					P
Location	Operating and fault	Voltage (V)	Current (A)	Max. Power ¹⁾	Time (S)	PS class

IEC 62368-1						
Clause	Requirement + Test			Result - Remark		Verdict
	condition			(W)		
All circuits except for output circuits (Output connector)	--	--	--	--	--	PS3 (Declared)
USB-C Output terminal: 5V	Normal	5.2	3.8	17.22	5	PS2
	U1 pin 1-4 SC	0	0	0	3	PS1
	U3 pin 1-5 SC	0	0	0	3	PS1
	D3 SC	0	0	0	3	PS1
	D1 SC	0	0	0	3	PS1
	R8 SC	0	0	0	3	PS1
USB-C Output terminal: 9V	Normal	9.07	3.0	25.33	5	PS2
	U1 pin 1-4 SC	0	0	0	3	PS1
	U3 pin 1-5 SC	0	0	0	3	PS1
	D3 SC	0	0	0	3	PS1
	D1 SC	0	0	0	3	PS1
	R8 SC	0	0	0	3	PS1
USB-C Output terminal: 12V	Normal	12.15	2.4	26.62	5	PS2
	U1 pin 1-4 SC	0	0	0	3	PS1
	U3 pin 1-5 SC	0	0	0	3	PS1
	D3 SC	0	0	0	3	PS1
	D1 SC	0	0	0	3	PS1
	R8 SC	0	0	0	3	PS1
USB-A Output terminal: 5V	Normal	5.03	3.5	16.37	5	PS2
	U1 pin 1-4 SC	0	0	0	3	PS1
	U3 pin 1-5 SC	0	0	0	3	PS1
	D3 SC	0	0	0	3	PS1
	D1 SC	0	0	0	3	PS1
	R8 SC	0	0	0	3	PS1
USB-A Output terminal: 9V	Normal	9.05	2.9	24.31	5	PS2
	U1 pin 1-4 SC	0	0	0	3	PS1
	U3 pin 1-5 SC	0	0	0	3	PS1
	D3 SC	0	0	0	3	PS1

IEC 62368-1						
Clause	Requirement + Test	Result - Remark				Verdict
USB-A Output terminal: 12V	D1 SC	0	0	0	3	PS1
	R8 SC	0	0	0	3	PS1
	Normal	12.03	2.3	25.47	5	PS2
	U1 pin 1-4 SC	0	0	0	3	PS1
	U3 pin 1-5 SC	0	0	0	3	PS1
	D3 SC	0	0	0	3	PS1
	D1 SC	0	0	0	3	PS1
	R8 SC	0	0	0	3	PS1
Supplementary information: Abbreviation: SC= short circuit; OC= open circuit 1) Measured after 3 s for PS1 and measured after 5 s for PS2 and PS3.						

6.2.3.1	TABLE: Determination of Arcing PIS				P
Location		Open circuit voltage after 3 s (Vpk)	Measured r.m.s current (A)	Calculated value	Arcing PIS? Yes / No
All circuits except for output circuits (output connector)		--	--	--	Yes (declaration)
Supplementary information: N/A					

6.2.3.2	TABLE: Determination of resistive PIS			P
Location		Operating and fault condition	Dissipate power (W)	Resistive PIS? Yes / No
All internal circuits / components		--	--	Yes (declaration)
Supplementary information: Abbreviation: SC= short circuit; OC= open circuit				

8.5.5	TABLE: High pressure lamp				N/A
Lamp manufacturer	Lamp type	Explosion method	Longest axis of glass particle (mm)	Particle found beyond 1 m Yes / No	
--	--	--	--	--	
Supplementary information: N/A					

IEC 62368-1								
Clause	Requirement + Test				Result - Remark		Verdict	
9.6	TABLE: Temperature measurements for wireless power transmitters							N/A
Supply voltage (V)			--				—	
Max. transmit power of transmitter (W)			--				—	
Foreign objects	w/o receiver and direct contact		with receiver and direct contact		with receiver and at distance of 2 mm		with receiver and at distance of 5 mm	
	Object (°C)	Ambient (°C)	Object (°C)	Ambient (°C)	Object (°C)	Ambient (°C)	Object (°C)	Ambient (°C)
--	--	--	--	--	--	--	--	--
Supplementary information: N/A								

5.4.1.4, 9.3, B.1.5, B.2.6	TABLE: Temperature measurements							P
Supply voltage (V)				Condition A	Condition B	Condition C	—	
Ambient temperature during test T_{amb} (°C)				25.0	25.0	25.0	—	
Maximum measured temperature T of part/at:				T (°C)				Allowed T_{max} (°C)
Enclosure outside				48.5	50.4	50.1	120	
Enclosure inside				51.8	53.8	53.5	120	
L1 Body				92.6	97.6	96.7	130	
EC2 Body				90.2	95.4	94.4	105	
EC1 Body				92.9	97.4	96.5	105	
T1 Coil				97.0	102.3	100.8	110	
T1 Core				96.2	101.9	100.6	--	
EC4 Body				96.5	101.0	99.2	105	
PCB near U1				99.1	103.3	101.3	130	
PCB near U3				95.9	99.9	99.0	105	
PCB near BD1				97.5	102.7	101.9	130	
CY1 Body				93.3	97.5	96.4	125	
U2 Body				97.2	101.6	100.4	110	
Enclosure inside top near T1				89.7	92.6	89.4	120	

IEC 62368-1				
Clause	Requirement + Test	Result - Remark		Verdict
Enclosure outside top near T1	74.4	74.9	74.0	120
Enclosure inside side near T1	94.1	99.4	98.2	120
Enclosure outside side near T1	65.7	68.8	67.6	77
Plastic enclosure close to between USB-A and USB-C output port, outside	74.9	75.2	73.7	77
Enclosure inside bottom near T1	76.8	79.9	80.0	120
Enclosure outside bottom near T1	74.9	75.2	75.1	120
Supply voltage (V) :	Condition D	Condition E	Condition F	—
Ambient temperature during test Tamb (°C) :	25.0	25.0	25.0	—
Maximum measured temperature T of part/at:	T (°C)			Allowed T_{max} (°C)
Enclosure outside	47.2	47.5	47.4	120
Enclosure inside	50.3	50.7	50.4	120
L1 Body	88.5	89.2	88.5	130
EC2 Body	86.1	86.9	86.2	105
EC5 Body	86.5	87.1	86.3	105
T1 Coil	90.9	91.9	91.2	110
T1 Core	90.4	91.8	90.8	--
EC4 Body	88.2	90.1	89.0	105
PCB near U1	89.5	92.5	91.2	130
PCB near U3	87.1	88.6	87.9	105
PCB near BD1	94.0	94.7	93.9	130
CY1 Body	86.8	86.9	86.2	125
U2 Body	89.9	89.8	89.2	110
Enclosure inside top near T1	83.9	85.1	84.3	120
Enclosure outside top near T1	70.2	72.0	70.8	120
Enclosure inside side near T1	88.6	89.6	89.0	120
Enclosure outside side near T1	61.8	62.6	61.3	77
Plastic enclosure close to between USB-A and USB-C output port, outside	65.3	66.5	62.1	77

IEC 62368-1							
Clause	Requirement + Test				Result - Remark		Verdict
Enclosure inside bottom near T1			74.4	74.8	74.1	120	
Enclosure outside bottom near T1			72.5	72.5	71.8	120	
Temperature T of winding:	t ₁ (°C)	R ₁ (Ω)	t ₂ (°C)	R ₂ (Ω)	T (°C)	Allowed T _{max} (°C)	Insulation class
--	--	--	--	--	--	--	--
Supplementary information: Condition A: Input: 90Vac/60Hz, Load: USB-C: 9Vdc, 2.22A+Socket: 16A. Condition B: Input: 90Vac/60Hz, Load: USB-A:9Vdc, 2.22A+Socket: 16A. Condition C: Input: 90Vac/60Hz, Load: USB-C+USB-A: 5Vdc, 3A+Socket: 16A. Condition D: Input: 275Vac/60Hz, Load: USB-C: 9Vdc, 2.22A+Socket: 16A. Condition E: Input: 275Vac/60Hz, Load: USB-A:9Vdc, 2.22A+Socket: 16A. Condition F: Input: 275Vac/60Hz, Load: USB-C+USB-A: 5Vdc, 3A+Socket: 16A.							

B.2.5		TABLE: Input test						P
U (V)	Hz	I (A)	I rated (A)	P (W)	P rated (W)	Fuse No	I fuse (A)	Condition/status
90	50	16.385	--	18.28	--	F1	0.385	Load: USB-C: 5Vdc, 3A
90	60	16.400	--	18.28	--	F1	0.400	
100	50	16.356	0.5	18.20	--	F1	0.356	
100	60	16.362	0.5	18.23	--	F1	0.362	
250	50	16.187	0.5	18.26	--	F1	0.187	
250	60	16.189	0.5	18.27	--	F1	0.189	
275	50	16.173	--	18.33	--	F1	0.173	
275	60	16.176	--	18.36	--	F1	0.176	
90	50	16.450	--	22.53	--	F1	0.450	Load: USB-C: 9Vdc, 2.22A
90	60	16.460	--	22.60	--	F1	0.460	
100	50	16.411	0.5	22.39	--	F1	0.411	
100	60	16.418	0.5	22.46	--	F1	0.418	
250	50	16.214	0.5	22.39	--	F1	0.214	
250	60	16.217	0.5	22.41	--	F1	0.217	
275	50	16.192	--	22.38	--	F1	0.192	
275	60	16.198	--	22.42	--	F1	0.198	
90	50	16.449	--	23.10	--	F1	0.449	Load: USB-C: 12Vdc, 1.67A
90	60	16.454	--	23.21	--	F1	0.454	

IEC 62368-1								
Clause		Requirement + Test				Result - Remark		Verdict
100	50	16.413	0.5	22.93	--	F1	0.413	
100	60	16.414	0.5	22.98	--	F1	0.414	
250	50	16.208	0.5	22.75	--	F1	0.208	
250	60	16.212	0.5	22.78	--	F1	0.212	
275	50	16.191	--	22.89	--	F1	0.191	
275	60	16.193	--	22.93	--	F1	0.193	
90	50	16.392	--	18.46	--	F1	0.392	Load: USB-A: 5Vdc, 3A
90	60	16.402	--	18.47	--	F1	0.402	
100	50	16.355	0.5	18.37	--	F1	0.355	
100	60	16.367	0.5	18.39	--	F1	0.367	
250	50	16.190	0.5	18.40	--	F1	0.190	
250	60	16.191	0.5	18.42	--	F1	0.191	
275	50	16.172	--	18.47	--	F1	0.172	
275	60	16.175	--	18.50	--	F1	0.175	
90	50	16.357	--	21.61	--	F1	0.357	Load: USB-A: 9Vdc, 2.22A
90	60	16.361	--	21.64	--	F1	0.361	
100	50	16.332	0.5	21.35	--	F1	0.332	
100	60	16.337	0.5	21.39	--	F1	0.337	
250	50	16.191	0.5	21.11	--	F1	0.191	
250	60	16.194	0.5	21.12	--	F1	0.194	
275	50	16.176	--	21.15	--	F1	0.176	
275	60	16.180	--	21.18	--	F1	0.180	
90	50	16.352	--	21.30	--	F1	0.352	Load: USB-A: 12Vdc, 1.67A
90	60	16.357	--	21.32	--	F1	0.357	
100	50	16.331	0.5	21.13	--	F1	0.331	
100	60	16.334	0.5	21.16	--	F1	0.334	
250	50	16.191	0.5	20.95	--	F1	0.191	
250	60	16.192	0.5	20.99	--	F1	0.192	
275	50	16.175	--	21.01	--	F1	0.175	
275	60	16.178	--	21.03	--	F1	0.178	
90	50	16.403	--	18.87	--	F1	0.403	Load: USB-A+ USB-C: 5Vdc, 3A
90	60	16.418	--	18.88	--	F1	0.418	

IEC 62368-1							
Clause	Requirement + Test					Result - Remark	Verdict
100	50	16.367	0.5	18.77	--	F1	0.367
100	60	16.370	0.5	18.80	--	F1	0.370
250	50	16.195	0.5	18.85	--	F1	0.195
250	60	16.199	0.5	18.87	--	F1	0.199
275	50	16.181	--	18.93	--	F1	0.181
275	60	16.182	--	18.97	--	F1	0.182
Supplementary information: Equipment may be have rated current or rated power or both. Both should be measured.							

B.3, B.4 TABLE: Abnormal operating and fault condition tests						P
Ambient temperature T _{amb} (°C)..... :					25°C if not specified	—
Power source for EUT: Manufacturer, model/type, outputrating .. :					--	—
Component No.	Condition	Supply voltage (V)	Test time	Fuse no.	Fuse current (A)	Observation
BD1 Pin "1" to "4"	SC	275Vac	1s	F1	0	Unit shut down, F1 fuse open, no hazardous.
C1	SC	275Vac	1s	F1	0	Unit shut down, F1 fuse open, no hazardous.
D1	SC	275Vac	1s	F1	0	Unit shut down, F1 fuse open, no hazardous.
D2	SC	275Vac	1s	F1	0	Unit shut down, F1 fuse open, no hazardous.
C7	SC	275Vac	1s	F1	0	Unit shut down, F1 fuse open, no hazardous.
R1	SC	275Vac	1s	F1	0	Unit shut down, F1 fuse open, no hazardous.
U1 pin 3-7	SC	275Vac	1s	F1	0	Unit shut down, F1 fuse open, no hazardous.
U1 pin 2-6	SC	275Vac	1s	F1	0	Unit shut down, F1 fuse open, no hazardous.
U1 pin 4-7	SC	275Vac	1s	F1	0	Unit shut down, F1 fuse open, no hazardous.
T1 Pin 1-2	SC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
T1 Pin 4-5	SC	275Vac	10mins	F1	0.002	Unit shut down, can be

Tel: (86)755-85277785

Fax: (86)755-23705230

E-mail: postmaster@aoc-cert.comWebsite: [Http://www.aoc-cert.com](http://www.aoc-cert.com)

TRF No. IEC 62368_1E

IEC 62368-1						
Clause	Requirement + Test				Result - Remark	Verdict
						recovery, no damaged, no hazardous.
T1 Pin A-B	SC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
U2 Pin 1-2	SC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
U2 Pin 3-4	SC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
U2 Pin 1	OC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
U2 Pin 3	OC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
U3 Pin 3-8	SC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
C4	SC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
R12	SC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
USB-A Output terminal "+", "-"	SC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
USB-C Output terminal "+", "-"	SC	275Vac	10mins	F1	0.002	Unit shut down, can be recovery, no damaged, no hazardous.
USB-C Output terminal: 5V	OL	275Vac	30mins	F1	0.232	Unit max load when output overload to 3.8A. Unit shut down immediately, no damaged, can be recovery, no hazardous.
USB-C Output terminal: 9V	OL	275Vac	30mins	F1	0.267	Unit max load when output overload to 3.0A. Unit shut down immediately, no damaged, can be recovery, no hazardous.

IEC 62368-1						
Clause	Requirement + Test			Result - Remark		Verdict
USB-C Output terminal: 12V	OL	275Vac	5h53mins	F1	0.193→ 0.224→ 0.269→ 0.295→ 0.002	Unit max load when output overload to 2.4A. T1 coil: 116.9°C T1 Bobbin: 112.3°C Plastic enclosure near top T1, outside: 85.3 °C Plastic enclosure close to between USB-A and USB-C output port, outside: 82.5 °C Ambient: 25°C Unit shut down immediately, no damaged, can be recovery, no hazardous.
Supplementary information: N/A						

M.3	TABLE: Protection circuits for batteries provided within the equipment						N/A
Is it possible to install the battery in a reverse polarity position? :				No		—	
Equipment Specification	Charging						
	Voltage (V)			Current (A)			
	--			--			
Manufacturer/type	Battery specification						
	Non-rechargeable batteries		Rechargeable batteries				
	Discharging current (A)	Unintentional charging current (A)	Charging		Discharging current (A)	Reverse charging current (A)	
			Voltage (V)	Current (A)			
--	--	--	--	--	--	--	
Note: The tests of M.3.2 are applicable only when above appropriate data is not available.							
Specified battery temperature (°C) :				--		—	
Component No.	Fault condition	Charge/ discharge mode	Test time	Temp. (°C)	Current (A)	Voltage (V)	Observation
--	--	--	--	--	--	--	--
Supplementary information:							
Abbreviation: SC= short circuit; OC= open circuit NL= no chemical leakage; NS= no spillage of liquid; NE= no explosion; NF= no emission of flame or expulsion of molten metal.							

M.4.2	TABLE: Charging safeguards for equipment containing a secondary lithium battery	N/A
--------------	--	-----

IEC 62368-1					
Clause	Requirement + Test			Result - Remark	Verdict
Maximum specified charging voltage (V) :				--	—
Maximum specified charging current (A) :				--	—
Highest specified charging temperature (°C) :				--	—
Lowest specified charging temperature (°C) :				--	—
Battery manufacturer/type	Operating and fault condition	Measurement			Observation
		Charging voltage (V)	Charging current (A)	Temp. (°C)	
--	--	--	--	--	--
Supplementary information:					
Abbreviation: SC= short circuit; OC= open circuit; MSCV= maximum specified charging voltage; MSCC= maximum specified charging current; HSCT= highest specified charging temperature; LSCT= lowest specified charging temperature					

Q.1	TABLE: Circuits intended for interconnection with building wiring (LPS)						P
Output Circuit	Condition	U _{oc} (V)	Time (s)	I _{sc} (A)		S (VA)	
				Meas.	Limit	Meas.	Limit
USB-C Output terminal: 5V	Normal	5.2	5	3.8	8	17.22	100
	U1 pin 1-4 SC	0	5	0	8	0	100
	U3 pin 1-5 SC	0	5	0	8	0	100
	D3 SC	0	5	0	8	0	100
	D1 SC	0	5	0	8	0	100
	R8 SC	0	5	0	8	0	100
USB-C Output terminal: 9V	Normal	9.07	5	3	8	25.33	100
	U1 pin 1-4 SC	0	5	0	8	0	100
	U3 pin 1-5 SC	0	5	0	8	0	100
	D3 SC	0	5	0	8	0	100
	D1 SC	0	5	0	8	0	100
	R8 SC	0	5	0	8	0	100
USB-C Output terminal: 12V	Normal	12.15	5	2.4	8	26.62	100
	U1 pin 1-4 SC	0	5	0	8	0	100
	U3 pin 1-5 SC	0	5	0	8	0	100
	D3 SC	0	5	0	8	0	100
	D1 SC	0	5	0	8	0	100

IEC 62368-1							
Clause	Requirement + Test			Result - Remark			Verdict
	R8 SC	0	5	0	8	0	100
USB-A Output terminal: 5V	Normal	5.03	5	3.5	8	16.37	100
	U1 pin 1-4 SC	0	5	0	8	0	100
	U3 pin 1-5 SC	0	5	0	8	0	100
	D3 SC	0	5	0	8	0	100
	D1 SC	0	5	0	8	0	100
	R8 SC	0	5	0	8	0	100
USB-A Output terminal: 9V	Normal	9.05	5	2.9	8	24.31	100
	U1 pin 1-4 SC	0	5	0	8	0	100
	U3 pin 1-5 SC	0	5	0	8	0	100
	D3 SC	0	5	0	8	0	100
	D1 SC	0	5	0	8	0	100
	R8 SC	0	5	0	8	0	100
USB-A Output terminal: 12V	Normal	12.03	5	2.3	8	25.47	100
	U1 pin 1-4 SC	0	5	0	8	0	100
	U3 pin 1-5 SC	0	5	0	8	0	100
	D3 SC	0	5	0	8	0	100
	D1 SC	0	5	0	8	0	100
	R8 SC	0	5	0	8	0	100
Supplementary Information: Abbreviation: SC= short circuit; OC= open circuit							

T.2, T.3, T.4, T.5	TABLE: Steady force test						P
Part/Location	Material	Thickness (mm)	Probe	Force (N)	Test Duration (s)	Observation	
Internal components / wire	--	--	V.2	10	5	No reduction the clearances and creepage distances.	
Top enclosure	Plastic	Min. 1.0	--	250	5	No damage, No hazard	
Supplementary information: N/A							

T.6, T.9	TABLE: Impact test						P
----------	--------------------	--	--	--	--	--	---

IEC 62368-1				
Clause	Requirement + Test		Result - Remark	Verdict
Location/part	Material	Thickness (mm)	Height (mm)	Observation
Top enclosure	Plastic	Min. 1.0	1300	No damage, No hazard
Supplementary information: N/A				

T.7	TABLE: Drop test				N/A
Location/part	Material	Thickness (mm)	Height (mm)	Observation	
Supplementary information: N/A					


T.8	TABLE: Stress relief test					P
Location/Part	Material	Thickness (mm)	Oven Temperature (°C)	Duration (h)	Observation	
Completed sample	Plastic	Min. 1.0	100	7	No damaged, the hazardous live parts cannot be touched.	
Supplementary information: N/A						

X	TABLE: Alternative method for determining minimum clearances distances			N/A
Clearance distanced between:	Peak of working voltage (V)	Required cl (mm)	Measured cl (mm)	
--	--	--	--	
Supplementary information: N/A				

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict

4.1.2	TABLE: Critical components information					P
Object / part No.	Manufacturer / trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾	
Plastic enclosure	SABIC INNOVATIVE PLASTICS US L L C	940(f1)(gg*)	120 °C, V-0, Min. thickness: 1.5 mm	UL 94 UL 746C	UL E121562	
PCB	LONGYAN CITY HUNG TO PCB CO LTD	HT-M1, HT-D1	V-0, 130 °C	UL 94	UL E327182	
Fuse (F1)	XC Electronics (Shen Zhen) Corp. Ltd.	4T	T2A, 250Vac	IEC/EN 60217-1, IEC/EN 60217-3	VDE 40029295	
Internal wire	Interchangeable	Interchangeable	Min. 300 V, Min. 80 °C, Min. 22 AWG, Min. VW-1	UL 758	UL	
Bridge rectifier (BD1)	Shenzhen Walder Semiconductor Co., Ltd.	WRABS20M	Min. 1.0 A, Min. 1000 V	IEC/EN 62368-1	Test with appliance	
(Alternative)	Nanjing Zhongbao Electronic Co., Ltd.	FTB10S-20	Min. 1.0 A, Min. 1000 V	IEC/EN 62368-1	Test with appliance	
Electrolytic Capacitor (C1, C2)	Fuzhiqing Electronics (Shenzhen) Co., Ltd.	CH	Each Min. 400 V, Max. 27 uF, 105 °C	IEC/EN 62368-1	Test with appliance	
Line chock (L1)	Shenzhen shuo pu te electronic technology Co., Ltd	TΦ6*12	130 °C	IEC/EN 62368-1	Tested with appliance	
Y-Capacitor (CY1)	Sichuan TRX Technology Co., Ltd.	TRX	Max. 2200 pF, Min. 400 Vac, 125 °C, Y1 type.	IEC/EN 60384-14	ENEC-02084-M2	
(Alternative)	Huizhou Jingqin Electronic Components Co., Ltd.	SMD series	Max. 2200 pF, Min. 400 Vac, 125 °C, Y1 type.	IEC/EN 60384-14	ENEC-04145-M1	

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
Optocoupler (U2)	Everlight Electronics Co., Ltd.	EL817	Double protection optical isolators, providing 4000 vac isolation Dti. ≥0.4 mm, ext.cl.=ext.cr.≥7.6mm, 110 °C	IEC/EN 60747-5-5	VDE 132249
Transformer (T1)	Guangxi Qinzhou Xingda Weiye Technology Co Ltd	W-001-GaN	Class B	IEC/EN 62368-1	Test with appliance
- Bobbin	CHANG CHUN PLASTICS CO LTD	T375J(G5)(G6)	Phenolic, V-0, 150 °C, Min. Thickness 0.7 mm	UL 94	UL E59481
- Magnet wire	HUIZHOU CITY DENGGAODA ELECTROTECH CO LTD	X UEW	130 °C; MW 79-C	UL 1446	UL E253843
(Alternative)	Interchangeable	Interchangeable	130 °C; MW 79-C	UL 1446	UL
-Triple insulation wire	Shenzhen Kaizhong Hedong New Materials Co., Ltd.	TIW-B	130 °C	IEC/EN 62368-1	VDE 40038861
- Insulation tape	JINGJIANG JINGYI ADHESIVE PRODUCT CO LTD	JY25-A (b)	130 °C	UL 510A	UL E246950
-Tubing	Fluotech Industrial (Huizhou) Co Ltd	TFT	200 °C, min. 300 V	UL 224	UL E175982
-Varnish	ZHUHAI CHANGXIAN NEW MATERIALS TECHNOLOGY CO LTD	E962	MW 28-C, 130 °C	UL 1446	UL E335405
Supplementary information: 1) Provided evidence ensures the agreed level of compliance. See OD-2039. 2) Description line content is optional. Main line description needs to clearly detail the component used for testing.					


Attachment No.1**Product Photos**Details of: Overview for model ZBG814Details of: Overview for model ZBG814



Tel: (86)755-85277785



Fax: (86)755-23705230



E-mail: postmaster@aac-cert.comWebsite: <http://www.aac-cert.com>


TRF No. IEC 62368_1E

Attachment No.1**Product Photos**Details of: Overview for model ZBG814Details of: Overview for model ZBG814

Attachment No.1**Product Photos**Details of: Overview for model ZBG814Details of: Overview for model ZBG814

Attachment No.1**Product Photos**Details of: Overview for model ZBG814Details of: Overview for model ZBG814

Attachment No.1**Product Photos**Details of: Overview for model ZBG814Details of: Overview for model ZBG814

Attachment No.1**Product Photos**Details of: Overview for model ZBG814**- End of report -**