



TEST REPORT
IEC 60598-2-4
Luminaires, Part 2: Particular requirements
Section 4: Portable general purpose luminaires

Report Number. : AOC251023004S

Date of issue : 2025-10-29

Total number of pages : 44 pages

Name of Testing Laboratory preparing the Report : Shenzhen AOCE Electronic Technology Service Co., Ltd
Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China

Applicant's name : Dongguan Excel Jointure Acrylic Products LTD.
Address : Shang Keng Industrial District, Chang Ping Town Dongguan Guangdong Province, PRC

Test specification:

Standard : ☒ IEC 60598-2-4:2017
☒ IEC 60598-1:2020
☒ European Group Differences And National Differences

Test procedure : Type testing

Non-standard test method : N/A

Test Report Form No. : IEC60598_2_4I

Test Report Form(s) Originator : UL(US)

Master TRF : 2021-06-10

Copyright © 2021 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

General disclaimer:

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the Testing Laboratory, responsible for this Test Report

Test item description	Promotion materials, Innovative display material, Creative props, BK-Innovative props Dual Holder Combined with Strong Mobile Phone Alarm	
Trade Mark	HONOR	
Manufacturer	Dongguan Excel Jointure Acrylic Products LTD. Shang Keng Industrial District, Chang Ping Town Dongguan Guangdong Province, PRC	
Model/Type reference.....	9711AFWY	
Ratings.....	100-240 V~, 50/60 Hz, 30 W , Class II, IP 20, ta:25 °C	
Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):		
☒	Testing Laboratory:	Shenzhen AOCE Electronic Technology Service Co., Ltd
Testing location/ address		Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China
Tested by (name, function, signature)		ZhiCong Xian Technical Engineer <i>ZhiCong Xian</i>
Approved by (name, function, signature) ..		Robin Liu Technical Manager <i>Robin. Liu</i>
☐	Testing procedure: CTF Stage 1:	N/A
Testing location/ address		
Tested by (name, function, signature)		
Approved by (name, function, signature) ..		
☐	Testing procedure: CTF Stage 2:	N/A
Testing location/ address		
Tested by (name + signature).....		
Witnessed by (name, function, signature) . :		
Approved by (name, function, signature) .. :		
☐	Testing procedure: CTF Stage 3:	N/A
☐	Testing procedure: CTF Stage 4:	N/A
Testing location/ address		
Tested by (name, function, signature)		
Witnessed by (name, function, signature) . :		
Approved by (name, function, signature) .. :		
Supervised by (name, function, signature) :		

Tel: (86)755-85277785

Fax: (86)755-23705230


E-mail: postmaster@aoc-cert.comWebsite: <http://www.aoc-cert.com>

TRF No. IEC60598_2_4I

List of Attachments (including a total number of pages in each attachment): Attachment No.1: European Group Differences And National Differences Attachment No.2: Clause 13 of IEC 62031 Attachment No.3: Photo document.	
Summary of testing:	
Tests performed (name of test and test clause): - All testing were performed on model 9711AFWY - EN 60598-2-4:2018 - EN IEC 60598-1:2024+A11:2024	Testing location: Shenzhen AOCE Electronic Technology Service Co., Ltd Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China
Summary of compliance with National Differences (List of countries addressed): N/A	
Statement concerning the uncertainty of the measurement systems used for the tests ☐ Internal procedure used for type testing through which traceability of the measuring uncertainty has been established: Procedure number, issue date and title: N/A ☒ Statement not required by the standard used for type testing	

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.



Test item particulars..... :	
Classification of installation and use..... :	Portable luminaires
Supply Connection	Adapter
Possible test case verdicts:	
- test case does not apply to the test object..... :	N/A
- test object does meet the requirement..... :	P (Pass)
- test object does not meet the requirement..... :	F (Fail)
Testing..... :	
Date of receipt of test item	2025-10-09
Date (s) of performance of tests	2025-10-09 to 2025-10-29
General remarks:	
The tested sample(s) and the sample information are provided by the client. "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Note: EN Group Differences together with National Differences and Special National Conditions, if any, are in the Appendix to the main body of this TRF. Throughout this report a ☐ comma / ☒ point is used as the decimal separator. The test report only allows to be revised only within the report defined retention period unless standard or regulation was withdrawn or invalid. When determining for test conclusion, measurement uncertainty of tests has been considered. Clause numbers between brackets refer to clauses in IEC 60598-1. Note: clauses marked “*” not included in CNAS scope.	
Manufacturer's Declaration per sub-clause 4.2.5 of IEC 60598-1:	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided :	☐ Yes ☒ Not applicable
When differences exist; they shall be identified in the General product information section.	
Name and address of factory (ies) : Same as manufacturer	

General product information and other remarks:

Indoor use only portable luminaires.

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.4 (0)	GENERAL TEST REQUIREMENTS		-
4.4 (0.3)	More sections applicable	Yes ☐ No ☒ Section/s:	—
4.4 (0.5)	Components	(see Annex 1)	—
4.4 (0.7)	Information for luminaire design in light sources standards		—
4.4 (0.7.2)	Light source safety standard	IEC 62031	—
	Luminaire design in the light source safety standard		P
4.5 (2)	CLASSIFICATION OF LUMINAIRES		P
4.5 (2.2)	Type of protection	Class II	P
4.5 (2.3)	Degree of protection.....	IP 20	P
4.5 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces	Yes ☒ No ☐	—
4.5 (2.5)	Luminaire for normal use	Yes ☒ No ☐	—
	Luminaire for rough service	Yes ☐ No ☒	—
4.5.1 (-)	Ordinary luminaire classified “for indoor use only” ...	Yes ☒ No ☐	—
	Luminaires other than ordinary classified “for indoor use only”	Yes ☐ No ☒	
	Luminaires other than ordinary classified for “outdoor use” and “for indoor use”	Yes ☐ No ☒	
4.5.2 (-)	Portable luminaire for outdoor use classified IPX4 or higher		N/A
4.5.3 (-)	Luminaires designed for standing on a floor or table classified as suitable for direct mounting on normally flammable surfaces		P
4.6 (3)	MARKING		P
4.6 (3.2)	Mandatory markings		P
	Position of the marking		P
	Format of symbols/text		P
4.6 (3.3)	Additional information		P
	Language of instructions		P
4.6 (3.3.1)	Combination luminaires		N/A
4.6 (3.3.2)	Nominal frequency in Hz		N/A
4.6 (3.3.3)	Operating temperature		N/A
4.6 (3.3.5)	Wiring diagram		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.6 (3.3.6)	Special conditions		N/A
4.6 (3.3.7)	Metal halide lamp luminaire – warning		N/A
4.6 (3.3.8)	Limitation for semi-luminaires		N/A
4.6 (3.3.9)	Power factor and supply current		N/A
4.6 (3.3.10)	Suitability for use indoors		P
4.6 (3.3.11)	Luminaires with remote control		N/A
4.6 (3.3.12)	Clip-mounted luminaire – warning		N/A
4.6 (3.3.13)	Specifications of protective shields		N/A
4.6 (3.3.14)	Symbol for nature of supply		P
4.6 (3.3.15)	Rated current of socket outlet		N/A
4.6 (3.3.16)	Rough service luminaire		N/A
4.6 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments		N/A
4.6 (3.3.18)	Non-ordinary luminaires with PVC cable		N/A
4.6 (3.3.19)	Protective conductor current in instructions, if applicable		N/A
4.6 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		N/A
4.6 (3.3.21)	Non replaceable and non-user replaceable light sources information provided		P
	Cautionary symbol		N/A
4.6 (3.3.22)	Controllable luminaires, classification of insulation provided		N/A
4.6 (3.3.23)	Luminaire without controlgear provided with necessary information for selection of appropriate component		N/A
4.6 (3.3.24)	If not supplied with terminal block, information on the packaging		N/A
4.6 (3.3.25)	Luminaires employing light sources emitting UV on mains wiring, information provided		N/A
4.6 (3.3.26)	Wall mounted luminaire using external flexible cable or cord longer than 0.3 m, information provided		N/A
4.6 (3.4)	Test with water		P
	Test with hexane		P
	Legible after test		P
	Label attached		P

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.6.1 (-)	Luminaire not suitable for outdoor application		N/A
	Required symbol		N/A
	Information in the instructions		N/A
4.6.2 (-)	Outdoor use, socket outlet incorporated in the luminaire		N/A
	Maximum power rating marked		N/A
	Position of the marking		N/A
4.7 (4)	CONSTRUCTION		P
4.7 (4.2)	Components replaceable without difficulty		P
4.7 (4.3)	Wireways smooth and free from sharp edges		P
4.7 (4.4)	Lampholders		N/A
4.7 (4.4.1)	Integral lampholder		N/A
4.7 (4.4.2)	Wiring connection		N/A
4.7 (4.4.3)	Lampholder for end-to-end mounting		N/A
4.7 (4.4.4)	Positioning		N/A
	- pressure test (N)		—
	After test the lampholder comply with relevant standard sheets and show no damage		N/A
	After test on single-capped lampholder the lampholder have not moved from its position and show no permanent deformation		N/A
	- bending test (N)		—
	After test the lampholder have not moved from its position and show no permanent deformation		N/A
4.7 (4.4.5)	Peak pulse voltage		N/A
4.7 (4.4.6)	Centre contact		N/A
4.7 (4.4.7)	Parts in rough service luminaires resistant to tracking		N/A
4.7 (4.4.8)	Lamp connectors		N/A
4.7 (4.4.9)	Caps and bases correctly used		N/A
4.7 (4.4.10)	Light source for lampholder or connection according IEC 60061 not connected another way		N/A
4.7 (4.5)	Starter holders		N/A
	Starter holder in luminaires other than class II		N/A
	Starter holder class II construction		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.7 (4.6)	Terminal blocks		N/A
	Tails		N/A
	Unsecured blocks		N/A
4.7 (4.7)	Terminals and supply connections		P
4.7 (4.7.1)	Contact to metal parts		P
4.7 (4.7.2)	Test 8 mm live conductor		N/A
	Test 8 mm earth conductor		N/A
4.7 (4.7.3)	Terminals for supply conductors		N/A
4.7 (4.7.3.1)	Welded method and material		N/A
	- stranded or solid conductor		N/A
	- spot welding		N/A
	- welding between wires		N/A
	- Type Z attachment		N/A
	- mechanical test according to 15.6.2		N/A
	- electrical test according to 15.6.3		N/A
	- heat test according to 15.6.3.2.3 and 15.6.3.2.4		N/A
4.7 (4.7.4)	Terminals other than supply connection		N/A
4.7 (4.7.5)	Heat-resistant wiring/sleeves		N/A
4.7 (4.7.6)	Multi-pole plug		N/A
	- test at 30 N		N/A
4.7 (4.8)	Switches		N/A
	- adequate rating		N/A
	- adequate fixing		N/A
	- polarized supply		N/A
	- compliance with IEC 61058-1 for electronic switches		N/A
4.7 (4.9)	Insulating lining and sleeves		N/A
4.7 (4.9.1)	Retainment		N/A
	Method of fixing :		N/A
4.7 (4.9.2)	Insulated linings and sleeves:		N/A
	Resistant to a temperature > 20 °C to the wire temperature or		N/A
	a) & c) Insulation resistance and electric strength		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	b) Ageing test. Temperature (°C)..... :		N/A
4.7 (4.10)	Double or reinforced insulation		P
4.7 (4.10.1)	No contact, mounting surface – accessible metal parts – wiring of basic insulation		P
	Safe installation fixed luminaires		N/A
	Capacitors and switches		N/A
	Interference suppression capacitors according to IEC 60384-14		N/A
4.7 (4.10.2)	Assembly gaps:		N/A
	- not coincidental		N/A
	- no straight access with test probe		N/A
4.7 (4.10.3)	Retainment of insulation:		P
	- fixed		P
	- unable to be replaced; luminaire inoperative		P
	- sleeves retained in position		N/A
	- lining in lampholder		N/A
4.7 (4.10.4)	Protective impedance device		N/A
	Double or reinforced insulation bridged by appropriate and at least two resistors or two Y2 capacitors or one Y1 capacitor		N/A
	Y1 or Y2 capacitors comply with IEC 60384-14		N/A
	Resistors comply with test (a) in 14.1 of IEC 60065		N/A
4.7 (4.11)	Electrical connections and current-carrying parts		P
4.7 (4.11.1)	Contact pressure		P
4.7 (4.11.2)	Screws:		N/A
	- self-tapping screws		N/A
	- thread-cutting screws		N/A
4.7 (4.11.3)	Screw locking:		N/A
	- spring washer		N/A
	- rivets		N/A
4.7 (4.11.4)	Material of current-carrying parts		P
4.7 (4.11.5)	No contact to wood or mounting surface		P
4.7 (4.11.6)	Electro-mechanical contact systems		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.7 (4.12)	Screws and connections (mechanical) and glands		P
4.7 (4.12.1)	Screws not made of soft metal		P
	Screws of insulating material		N/A
	Torque test: torque (Nm); part : Fixed enclosure screw: 0.5Nm		P
	Torque test: torque (Nm); part :		N/A
	Torque test: torque (Nm); part :		N/A
4.7 (4.12.2)	Screws with diameter < 3 mm screwed into metal		N/A
4.7 (4.12.4)	Locked connections:		N/A
	- fixed arms; torque (Nm) :		N/A
	- lampholder; torque (Nm) :		N/A
	- push-button switches; torque 0,8 Nm :		N/A
4.7 (4.12.5)	Screwed glands; force (Nm) :		N/A
4.7 (4.13)	Mechanical strength		P
4.7 (4.13.1)	Impact tests:		P
	- fragile parts; energy (Nm) :		N/A
	- other parts; energy (Nm) : Enclosure: 0.5 Nm		P
	1) live parts		P
	2) linings		N/A
	3) protection		P
	4) covers		P
4.7 (4.13.3)	Straight test finger		P
4.7 (4.13.4)	Rough service luminaires		N/A
	- IP54 or higher		N/A
	a) fixed		N/A
	b) hand-held		N/A
	c) delivered with a stand		N/A
	d) for temporary installations and suitable for mounting on a stand		N/A
4.7 (4.13.6)	Tumbling barrel		N/A
4.7 (4.14)	Suspensions, fixings and means of adjusting		N/A
4.7 (4.14.1)	Mechanical load:		N/A
	A) four times the weight		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	B) torque 2,5 Nm		N/A
	C) bracket arm; bending moment (Nm)		N/A
	D) load track-mounted luminaires		N/A
	E) clip-mounted luminaires, glass-shelve. Thickness (mm)		—
	Metal rod. diameter (mm)		N/A
	Fixed luminaire or independent control gear without fixing devices		N/A
4.7 (4.14.2)	Load to flexible cables		N/A
	Mass (kg)		—
	Stress in conductors (N/mm ²)		N/A
	Mass (kg) of semi-luminaire		N/A
	Bending moment (Nm) of semi-luminaire		N/A
4.7 (4.14.3)	Adjusting devices:		N/A
	- flexing test; number of cycles		N/A
	- strands broken		N/A
	- electric strength test afterwards		N/A
4.7 (4.14.4)	Telescopic tubes: cords not fixed to tube; no strain on conductors		N/A
4.7 (4.14.5)	Guide pulleys		N/A
4.7 (4.14.6)	Strain on socket-outlets		N/A
4.7 (4.15)	Flammable materials		P
	- glow-wire test 650°C	See Test Table 4.15 (13.3.2)	P
	- spacing ≥30 mm		N/A
	- screen withstanding test of 13.3.1		N/A
	- screen dimensions		N/A
	- no fiercely burning material		P
	- thermal protection		N/A
	- electronic circuits exempted		N/A
4.7 (4.15.2)	Luminaires made of thermoplastic material with lamp control gear		N/A
	a) construction		N/A
	b) temperature sensing control		N/A
	c) surface temperature		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.7 (4.16)	Luminaires for mounting on normally flammable surfaces		P
	No lamp control gear..... : (compliance with Section 12)		P
4.7 (4.16.1)	Lamp control gear spacing:		N/A
	- spacing 35 mm		N/A
	- spacing 10 mm		N/A
4.7 (4.16.2)	Thermal protection:		N/A
	- in lamp control gear		N/A
	- external		N/A
	- fixed position		N/A
	- temperature marked lamp control gear		N/A
4.7 (4.16.3)	Design to satisfy the test of 12.6..... : (see clause 12.6)		N/A
4.7 (4.17)	Drain holes		N/A
	Clearance at least 5 mm		N/A
4.7 (4.18)	Resistance to corrosion		N/A
4.7 (4.18.1)	- rust-resistance		N/A
4.7 (4.18.2)	- season cracking in copper		N/A
4.7 (4.18.3)	- corrosion of aluminium		N/A
4.7 (4.19)	Ignitors compatible with ballast		N/A
4.7 (4.20)	Rough service vibration		N/A
4.7 (4.21)	Protective shield		N/A
4.7 (4.21.1)	Shield fitted if tungsten halogen lamps or metal halide lamps		N/A
	Shield of glass if tungsten halogen lamps		N/A
4.7 (4.21.2)	Particles from a shattering lamp not impair safety		N/A
4.7 (4.21.3)	No direct path		N/A
4.7 (4.21.4)	Impact test on shield		N/A
	Glow-wire test on lamp compartment : See Test Table 4.15 (13.3.2)		N/A
4.7 (4.22)	Attachments to lamps not cause overheating or damage		N/A
4.7 (4.23)	Semi-luminaires comply Class II		N/A
4.7 (4.24)	Photobiological hazards		P
4.7 (4.24.1)	No excessive UV radiation if tungsten halogen lamps and metal halide lamps (Annex P)		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.7 (4.24.2)	Retinal blue light hazard		P
	Class of risk group assessed according to IEC/TR 62778		—
	Luminaires with E_{thr} :		N/A
	a) Fixed luminaires		N/A
	- distance x m, borderline between RG1 and RG2 .. :		N/A
	- marking and instruction according 3.2.23		N/A
	b) Portable and handheld luminaires		N/A
	- marking according 3.2.23 if RG1 exceeded at 200 mm according to IEC/TR 62778		N/A
	Portable luminaires for children IEC 60598-2-10 and Mains socket outlet nightlights IEC 60598-2-12 not exceed RG1 at 200 mm according to IEC/62778		N/A
4.7 (4.25)	Mechanical hazard		P
	No sharp point or edges		P
4.7 (4.26)	Short-circuit protection		N/A
4.7 (4.26.1)	Adequate means of uninsulated accessible SELV parts		N/A
4.7 (4.26.2)	Short-circuit test with test chain according 4.26.3		N/A
	Test chain not melt through		N/A
	Test sample not exceed values of Table 12.1 and 12.2		N/A
4.7 (4.27)	Terminal blocks with integrated screwless earthing contacts		N/A
	Test according Annex V		N/A
	Pull test of terminal fixing (20 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Pull test of mechanical connection (50 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Voltage drop test, resistance < 0,05 Ω		N/A
4.7 (4.28)	Fixing of thermal sensing control		N/A
	Not plug-in or easily replaceable type		N/A
	Reliably kept in position		N/A
	No adhesive fixing if UV radiations from a lamp can degrade the fixing		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Not outside the luminaire enclosure		N/A
	Test of adhesive fixing:		N/A
	Max. temperature on adhesive material (°C) :		—
	100 cycles between t min and t max		N/A
	Temperature sensing control still in position		N/A
4.7 (4.29)	Luminaires with non-replaceable light source		N/A
	Not possible to replace light source		N/A
	Live part not accessible after parts have been opened by hand or tools		N/A
4.7 (4.30)	Luminaires with non-user replaceable light source		P
	If protective cover provide protection against electric shock and marked with “caution, electric shock risk” symbol:		N/A
	Minimum two fixing means		P
4.7 (4.31)	Insulation between circuits		P
	Circuits insulated from LV supply fulfil requirements according 4.31.1 – 4.31.3		P
	Controllable luminaires requiring same level of insulation for all components, the insulation between control terminals and LV supply fulfil requirements according 4.31.1 – 4.31.3		N/A
4.7 (4.31.1)	SELV circuits		P
	Used SELV source		P
	Voltage ≤ ELV		P
	Insulating of SELV circuits from LV supply		P
	Insulating of SELV circuits from other non SELV circuits		N/A
	Insulating of SELV circuits from FELV		N/A
	Insulating of SELV circuits from other SELV circuits		N/A
	SELV circuits insulated from accessible parts according Table X.1		P
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Plugs and socket-outlets does not have protective conductor contact		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.7 (4.31.2)	FELV circuits		N/A
	Used FELV source		N/A
	Voltage $\leq$ ELV		N/A
	Insulating of FELV circuits from LV supply		N/A
	FELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Socket-outlets does not have protective conductor contact		N/A
4.7 (4.31.3)	Other circuits		N/A
	Other circuits insulated from accessible parts according Table X.1		N/A
	Class II construction with equipotential bonding for protection against indirect contacts with live parts:		N/A
	- conductive parts are connected together		N/A
	- test according 7.2.3		N/A
	- conductive part not cause an electric shock in case of an insulation fault		N/A
	- equipotential bonding in master/slave applications		N/A
	- master luminaire provided with terminal for accessible conductive parts of slave luminaires		N/A
	- slave luminaire constructed as class I		N/A
4.7 (4.32)	Overvoltage protective devices		N/A
	Comply with IEC 61643-11		N/A
	External to controlgear and connected to earth:		N/A
	- only in fixed luminaires		N/A
	- only connected to protective earth		N/A
4.7 (4.33)	Luminaire powered via information technology communication cabling		N/A
	Requirements for Class III luminaire		N/A
	Rated voltage within the range of ES1 and does not exceed maximum voltage of used connector		N/A
	Luminaire does not create any hazard from overvoltage	(see Annex 2)	N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.7 (4.34)	Electromagnetic fields (EMF)		P
	No harmful electromagnetic fields	Comply with cl.4.2.2 of IEC 62493	P
4.7 (4.35)	Protection against moving fan blades		N/A
	Test with a standard test finger		N/A
	Test with test probe acc. to Figure 13 (IEC 61032) for portable luminaire		N/A
	Blades rounded with radius ≥ 0.5 mm and:		N/A
	- hardness less than D60 Shore		N/A
	- peripheral speed less than 15 m/s		N/A
	- input power of fan ≤ 2 W at rated voltage		N/A
4.7 (4.36)	Track-mounted luminaires		N/A
	Test in accordance with Annex A of IEC60570:2003/AMD2:2019		N/A
4.7.1 (-)	Insulation not damaged when moving, adjusting or placing on support		P
4.7.2 (-)	Wiring fixed, to avoid rubbing		N/A
	Carrier or clips of insulation material or with insulating lining		N/A
4.7.3 (-)	Luminaire does not overturn:		P
	- at an angle of 6° for indoor use		P
	- at an angle 15° for outdoor use		N/A
4.7.4 (-)	Candlestick luminaires provided with switch		N/A
	Switch in candlestick luminaires with E5 or E10 lampholders switches all lamps on and off simultaneously		N/A
	Switch part of the luminaire or within 300 mm of the luminaire if with cord		N/A
4.7.5 (-)	Voltage not exceeding 23.6 V for E5 lampholders		N/A
	E10 lampholder voltage:		N/A
	- not exceeding 60 V for series connection) or		N/A
	- not exceeding 250 V for parallel connections		N/A
	Maximum rated wattage not exceed 100 W		N/A
4.7.6 (-)	Portable luminaires for outdoor use tails not provided		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.7.7 (-)	Portable luminaires for outdoor use, cable entries		N/A
4.7.8 (-)	Portable luminaires for outdoor use, socket-outlet degree of protection at least same as the luminaire but not less than IPX4.		N/A
	Degree of protection maintained with or without a plug inserted into the socket-outlet.		N/A
	Class II luminaires, mains socket-outlets comply with the standard and only allow connection to Class II luminaires		N/A
	Class I luminaires, mains socket-outlets comply with the standard and only allow connection to Class I or Class II luminaires		N/A
4.7.9 (-)	Lampholders and plugs resistant to tracking for luminaires for outdoor use	See Test Table 4.16 (13.4)	N/A
	Compliance to clause 13.4		N/A
4.8 (11)	CREEPAGE DISTANCES AND CLEARANCES		P
	Impulse withstand category (Normal category II) (Category III Annex U, Table U.1).....:	Category II ☒ Category III ☐	—
4.8 (11.2.1)	Category III according Annex U		N/A
	Protected against pollution, reduced creepage and clearance according Annex P of IEC 61347-1		N/A
4.7 (11.2.2)	Creepage distances for frequency up to 30 kHz..... :	See Test Table 4.7 (11.2) I	P
	Creepage distances for frequency over 30 kHz:		N/A
	- Controlgear marked with $\hat{U}_{OUT}$ and f_{UOUT} according IEC 61347-1, clause 7.1, item w)..... :	See Test Table 4.7 (11.2) II	N/A
	- Requirements according IEC 60664-4 for controlgear not covered by IEC 61347	See Test Table 4.7 (11.2) II	N/A
4.7 (11.2.3)	Clearances for frequency up to 30 kHz..... :	See Test Table 4.7 (11.2) I	P
	Clearances distances for frequency over 30 kHz:		N/A
	- Controlgear marked with U_P :	See Test Table 4.7 (11.2) II	N/A
	- Requirements according IEC 60664-4 for controlgear not covered by IEC 61347	See Test Table 4.7 (11.2) II	N/A
4.9 (7)	PROVISION FOR EARTHING		N/A
4.9 (7.2.1 + 7.2.3)	Accessible metal parts		N/A
	Metal parts in contact with supporting surface		N/A
	Resistance $< 0,5 \Omega$		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Self-tapping screws used		N/A
	Thread-forming screws		N/A
	Thread-forming screw used in a groove		N/A
	Earth makes contact first		N/A
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
	Protective earthing of the luminaire not via built-in control gear		N/A
4.8 (7.2.2 + 7.2.3)	Earth continuity in joints, etc.		N/A
4.9 (7.2.4)	Locking of clamping means		N/A
	Compliance with 4.7.3		N/A
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
4.9 (7.2.5)	Earth terminal integral part of connector socket		N/A
4.9 (7.2.6)	Earth terminal adjacent to mains terminals		N/A
4.9 (7.2.7)	Electrolytic corrosion of the earth terminal		N/A
4.9 (7.2.8)	Material of earth terminal		N/A
	Contact surface bare metal		N/A
4.9 (7.2.10)	Class II luminaire for looping-in		N/A
	Double or reinforced insulation to functional earth		N/A
4.9 (7.2.11)	Earthing core coloured green-yellow		N/A
	Length of earth conductor		N/A
4.9 (7.2.12)	PELV circuit connected to protective earth for functional purpose		N/A
4.10 (14)	SCREW TERMINALS		N/A
	Separately approved; component list	(see Annex 1)	N/A
	Part of the luminaire.....	(see Annex 3)	N/A
4.10 (15)	SCREWLESS TERMINALS AND ELECTRICAL CONNECTIONS		N/A
	Separately approved; component list	(see Annex 1)	N/A
	Part of the luminaire.....	(see Annex 4)	N/A
4.11 (5)	EXTERNAL AND INTERNAL WIRING		P
4.11 (5.2)	Supply connection and external wiring		P
4.11 (5.2.1)	Means of connection.....		P

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Outdoor luminaire has not PVC insulated external wiring if not class III or SELV ≤ 23.6 V a.c./60 V d.c. or protected from outdoor environment		N/A
4.11 (5.2.2)	Type of cable		N/A
	Nominal cross-sectional area (mm ²)		N/A
	Cables equal to IEC 60227 or IEC 60245		N/A
4.11 (5.2.3)	Type of attachment, X, Y or Z		N/A
4.11 (5.2.5)	Type Z not connected to screws		N/A
4.11 (5.2.6)	Cable entries:		N/A
	- suitable for introduction		N/A
	- adequate degree of protection		N/A
4.11 (5.2.7)	Cable entries through rigid material have rounded edges		N/A
4.11 (5.2.8)	Insulating bushings:		N/A
	- suitably fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- tubes or guards made of insulating material		N/A
4.11 (5.2.9)	Locking of screwed bushings		N/A
4.11 (5.2.10)	Cord anchorage:		N/A
	- covering protected from abrasion		N/A
	- clear how to be effective		N/A
	- no mechanical or thermal stress		N/A
	- no tying of cables into knots etc.		N/A
	- insulating material or lining		N/A
4.11 (5.2.10.1)	Cord anchorage for type X attachment:		N/A
	a) at least one part fixed		N/A
	b) types of cable		N/A
	c) no damaging of the cable		N/A
	d) whole cable can be mounted		N/A
	e) no touching of clamping screws		N/A
	f) metal screw not directly on cable		N/A
	g) replacement without special tool		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Glands not used as anchorage		N/A
	Labyrinth type anchorages		N/A
4.11 (5.2.10.2)	Adequate cord anchorage for type Y and type Z attachment		P
4.11 (5.2.10.3)	Tests:		P
	- impossible to push cable; unsafe		P
	- pull test: 25 times; pull (N)		P
	- torque test: torque (Nm)		P
	- displacement ≤ 2 mm		P
	- no movement of conductors		P
	- no damage of cable or cord		P
	- function independent of electrical connection		N/A
4.11 (5.2.11)	External wiring passing into luminaire		P
4.11 (5.2.12)	Looping-in terminals		N/A
4.11 (5.2.13)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		N/A
4.11 (5.2.14)	Mains plug same protection		P
	Class III luminaire plug		N/A
	No unsafe compatibility		P
4.11 (5.2.16)	Appliance inlets (IEC 60320)		N/A
	Installation couplers (IEC 61535)		N/A
	Other appliance inlet or connector according relevant IEC standard		N/A
4.11 (5.2.17)	No standardized interconnecting cables properly assembled		N/A
4.11 (5.2.18)	Used plug in accordance with		P
	- IEC 60083		P
	- other standard		N/A
4.11 (5.3)	Internal wiring		P
4.11 (5.3.1)	Internal wiring of suitable size and type		P
	Through wiring		N/A
	- not delivered/ mounting instruction		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	- factory assembled		N/A
	- socket outlet loaded (A)		N/A
	- temperatures.....	(see Annex 2)	N/A
	Green-yellow for earth only		N/A
4.11 (5.3.1.1)	Internal wiring connected directly to fixed wiring		N/A
	Cross-sectional area (mm ²)		N/A
	Insulation thickness		N/A
	Extra insulation added where necessary		N/A
4.11 (5.3.1.2)	Internal wiring connected to fixed wiring via internal current-limiting device		N/A
	Cross-sectional area (mm ²)		N/A
4.11 (5.3.1.3)	Double or reinforced insulation for class II		P
4.11 (5.3.1.4)	Conductors without insulation		N/A
4.11 (5.3.1.5)	SELV current-carrying parts		P
4.11 (5.3.1.6)	Insulation thickness other than PVC or rubber		N/A
4.11 (5.3.2)	Sharp edges etc.		P
	No moving parts of switches etc.		N/A
	Joints, raising/lowering devices		N/A
	Telescopic tubes etc.		N/A
	No twisting over 360°		P
4.11 (5.3.3)	Insulating bushings:		N/A
	- suitable fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- cables with protective sheath		N/A
4.11 (5.3.4)	Joints and junctions effectively insulated		P
4.11 (5.3.5)	Strain on internal wiring		P
4.11 (5.3.6)	Wire carriers		N/A
4.11 (5.3.7)	Wire ends not tinned		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Wire ends tinned: no cold flow		P
4.11 (5.4)	Test to determine suitability of conductors having a reduced cross-sectional area		N/A
	Under test the temperature of the luminaire wiring insulation not exceed the limits stated in Table 12.2	(see Annex 2)	N/A
	No damage to luminaire wiring after test		N/A
4.11.1 (-)	Cord anchorage of luminaire for indoor use made of glass or ceramic not fixed or integral		N/A
4.11.2 (-)	For Class I and Class II luminaires for indoor use, if:		N/A
	- mass < 1 kg (kg)		N/A
	- rated current ≤ 2,5 A (A)		N/A
	- cable length ≤ 2 m (m)		N/A
	- the nominal cross-sectional area of copper conductor ≥ 0,5 mm ² (mm ²)		N/A
4.11.3 (-)	Terminals, cord anchorage and inlet opening provided for luminaire for outdoor use delivered without a flexible cable or cord and a plug.		N/A
4.11.4 (-)	Non-detachable flexible cables or cords not lighter than type 245 IEC 57 for Class I and Class II luminaires for outdoor use.		N/A
4.12 (8)	PROTECTION AGAINST ELECTRIC SHOCK		P
4.12 (8.2.1)	Live parts not accessible		P
	Basic insulated parts not used on the outer surface without appropriate protection		N/A
	Basic insulated parts not accessible with standard test finger on portable, settable and adjustable luminaires		N/A
	Basic insulated parts not accessible with Ø 50 mm probe from outside, other types of luminaires		N/A
	Lamp and starter holders in portable and adjustable luminaires comply with double or reinforced insulation requirements		N/A
	Basic insulation only accessible under lamp or starter replacement		N/A
	Protection in any position		P
	Double-ended tungsten filament lamp		N/A
	Insulation lacquer not reliable		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Double-ended high pressure discharge lamp		N/A
	Relevant warning according to 3.2.18 fitted to the luminaire		N/A
4.12 (8.2.2)	Portable luminaire adjusted in most unfavourable position		P
4.12 (8.2.3.a)	Class II luminaire:		N/A
	- basic insulated metal parts not accessible during starter or lamp replacement		N/A
	- basic insulation not accessible other than during starter or lamp replacement		N/A
	- glass protective shields not used as supplementary insulation		N/A
4.12 (8.2.3.b)	BC lampholder of metal in class I luminaires is earthed		N/A
4.12 (8.2.3.c)	SELV circuits with exposed current carrying parts:		N/A
	Ordinary luminaire:		N/A
	- voltage under load (V)		N/A
	- no-load voltage (V)		N/A
	- touch current if applicable (mA)		N/A
	One conductive part insulated if required		N/A
	Other than ordinary luminaire:		N/A
	- nominal voltage (V)		N/A
	Class III luminaire only for connection to SELV		N/A
	Class III luminaire not provided with means for protective earthing		N/A
4.12 (8.2.4)	Portable luminaire have protection independent of supporting surface		P
4.12 (8.2.5)	Compliance with the standard test finger or relevant probe		P
4.12 (8.2.6)	Covers reliably secured		P
4.12 (8.2.7)	Luminaire other than below with capacitor > 0,5 μ F not exceed 50 V 1 min after disconnection		N/A
	Portable luminaire with capacitor > 0,1 μ F (0.25) not exceed 34 V 1 s after disconnection		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Other luminaires with capacitor > 0,1 μ F (0.25) with plug and track adaptors not exceed 60 V 5 s after disconnection		N/A
4.12. (-)	Class I luminaire with bayonet lampholder:		N/A
	1) cap not accessible with test finger		N/A
	2) metal lampholder is earthed		N/A

4.13 (12)	ENDURANCE TEST AND THERMAL TEST		P
4.13 (-)	If IP > IP 20 relevant test of (12.4), (12.5), (12.6) and (12.7) after (9.2) before (9.3) specified in 4.13		—
4.13 (12.2)	Selection of lamps and ballasts		—
	Lamp used according Annex B.....	See Annex 2 for lamp used	—
	Controlgear if separate and not supplied.....	See Annex 2 for controlgear used	—
4.13 (12.3)	Endurance test:		P
	a) mounting-position	Normal mounting	—
	b) test temperature (°C)		—
	c) total duration (h).....		—
	d) if not equipped with controlgear, constant voltage/current (V) or (A)		—
	e) luminaire ceases to operate		—
4.13 (12.3.2)	After endurance test:		P
	- no part unserviceable		P
	- luminaire not unsafe		P
	- no damage to track system		N/A
	- marking legible		P
	- no cracks, deformation etc.		P
4.13 (12.4)	Thermal test (normal operation).....	(see Annex 2)	P
4.13 (12.5)	Thermal test (abnormal operation)	(see Annex 2)	N/A
4.13 (12.6)	Thermal test (failed lamp control gear condition):		N/A
4.13 (12.6.1)	Through wiring or looping-in wiring loaded by a current of (A)		—
	- case of abnormal conditions.....		—

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	- electronic lamp control gear		N/A
	- measured winding temperature (°C): at 1,1 Un		—
	- measured mounting surface temperature (°C) at 1,1 Un		N/A
	- calculated mounting surface temperature (°C)		N/A
	- track-mounted luminaires		N/A
4.13 (12.6.2)	Temperature sensing control		N/A
	- case of abnormal conditions.....		—
	- thermal link		N/A
	- manual reset cut-out		N/A
	- auto reset cut-out		N/A
	- measured mounting surface temperature (°C).....		N/A
	- track-mounted luminaires		N/A
4.13 (12.7)	Thermal test (failed lamp control gear in plastic luminaires):		N/A
4.13 (12.7.1)	Luminaire without temperature sensing control		N/A
4.13 (12.7.1.1)	Luminaire with fluorescent lamp ≤ 70W		N/A
	Test method 12.7.1.1 or Annex W		—
	Test according to 12.7.1.1:		N/A
	- case of abnormal conditions.....		—
	- Ballast failure at supply voltage (V)		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
	Test according to Annex W:		N/A
	- case of abnormal conditions.....		—
	- measured winding temperature (°C): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part (°C).....		—
	Ball-pressure test	See Table 4.15 (13.2.1)	N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.13 (12.7.1.2)	Luminaire with discharge lamp, fluorescent lamp > 70W, transformer > 10 VA		N/A
	- case of abnormal conditions.....:		—
	- measured winding temperature (°C): at 1,1 Un.....:		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....:		—
	- calculated temperature of fixing point/exposed part (°C).....:		—
	Ball-pressure test	See Table 4.15 (13.2.1)	N/A
4.13 (12.7.1.3)	Luminaire with short circuit proof transformers ≤ 10 VA		N/A
	- case of abnormal conditions.....:		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
4.13 (12.7.2)	Luminaire with temperature sensing control		N/A
	- thermal link	Yes ☐ No ☐	—
	- manual reset cut-out	Yes ☐ No ☐	—
	- auto reset cut-out.....:	Yes ☐ No ☐	—
	- case of abnormal conditions.....:		—
	- highest measured temperature of fixing point/exposed part (°C):.....:		—
	Ball-pressure test:	See Table 4.15 (13.2.1)	N/A
4.13 (-)	Indoor use luminaire, Test overturned position (overturns < 15°)		P
4.14 (9)	RESISTANCE TO DUST AND MOISTURE		P
4.14 (-)	If IP > IP 20 the order of tests as specified in clause 4.12		N/A
4.14 (9.2)	Tests for ingress of dust, solid objects and moisture:		N/A
	- classification according to IP	IP 20	—
	- mounting position during test.....:		—
	- fixing screws tightened; torque (Nm)		—
	- tests according to clauses		—
	- electric strength test afterwards		P
	a) no deposit in dust-proof luminaire		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	b) no talcum in dust-tight luminaire		N/A
	c) no trace of water on current-carrying parts or on insulation where it could become a hazard		N/A
	c.1) For luminaires without drain holes – no water entry		N/A
	c.2) For luminaires with drain holes – no hazardous water entry		N/A
	d) no water in watertight or pressure watertight luminaire		N/A
	e) no contact with live parts (IP 2X)	No live parts	N/A
	e) no entry into enclosure (IP 3X and IP 4X)		N/A
	e) no contact with live parts through drain holes and ventilation slots (IP3X and IP4X)		N/A
	f) no trace of water on part of lamp requiring protection from splashing water		N/A
	g) no damage of protective shield or glass envelope		N/A
4.14 (9.3)	Humidity test 48 h		P
4.14 (-)	Portable luminaire for outdoor use tested in the most unfavourable of the overturned positions likely to occur		N/A
4.15 (10)	INSULATION RESISTANCE AND ELECTRIC STRENGTH		P
4.15 (10.2.1)	Insulation resistance test		P
	Cable or cord covered by metal foil or replaced by a metal rod of mm Ø		—
	Insulation resistance (MΩ)		—
	SELV		P
	- between current-carrying parts of different polarity :	>100 MΩ	P
	- between current-carrying parts and mounting surface	>100 MΩ	P
	- between current-carrying parts and metal parts of the luminaire	>100 MΩ	P
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts		N/A
	- Insulation bushings as described in Section 5		N/A
	Other than SELV		P
	- between live parts of different polarity	>100 MΩ	P

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	- between live parts and mounting surface	>100 MΩ	P
	- between live parts and metal parts	>100 MΩ	P
	- between live parts of different polarity through action of a switch		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts		N/A
	- Insulation bushings as described in Section 5		N/A
4.15 (10.2.2)	Electric strength test		P
	Dummy lamp		N/A
	Luminaires with ignitors after 24 h test		N/A
	Luminaires with manual ignitors		N/A
	Test voltage (V).....		N/A
	SELV		P
	- between current-carrying parts of different polarity :	500 V	P
	- between current-carrying parts and mounting surface	500 V	P
	- between current-carrying parts and metal parts of the luminaire	500 V	P
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts		N/A
	- Insulation bushings as described in Section 5		N/A
	Other than SELV		P
	- between live parts of different polarity	1480 V	P
	- between live parts and mounting surface	2960 V	P
	- between live parts and metal parts	2960 V	P
	- between live parts of different polarity through action of a switch		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts		N/A
	- Insulation bushings as described in Section 5		N/A
4.15 (10.3)	Touch current or protective conductor current (mA):	Touch current : 0.01 mA	P

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.16 (13)	RESISTANCE TO HEAT, FIRE AND TRACKING		P
4.16 (13.2.1)	Ball-pressure test	See Test Table 4.15 (13.2.1)	P
4.16 (13.3.1)	Needle-flame test (10 s).....	See Test Table 4.15 (13.3.1)	N/A
4.16 (13.3.2)	Glow-wire test (650°C).....	See Test Table 4.15 (13.3.2)	P
4.16 (13.4)	Proof tracking test (IEC 60112)	See Test Table 4.15 (13.4)	N/A

IEC 60598-2-4							
Clause	Requirement + Test				Result - Remark		Verdict
4.7 (11.2)	TABLE I: Creepage distances and clearances						P
	Minimum distances (mm) for a.c. up to 30 kHz sinusoidal voltages						P
	Applicable part of IEC 60598-1 Table 11.1A*, 11.1B* and 11.2*						P
	Insulation type **	Measured clearance	Required		Measured creepage	Required	
			clearance	*Table		creepage	*Table
Distance 1:	B	> 1.5	1.5	11.1A	> 2.5	2.5	11.1B
Working voltage (V)					240 V		—
PTI					< 600 ☒ ≥ 600 ☐		—
Pulse voltage if applicable (kV)					-		—
Supplementary information: Between L and N							
Distance 2:	R	> 3.0	3.0	11.1A	> 5.0	5.0	11.1B
Working voltage (V)					240 V		—
PTI					< 600 ☐ ≥ 600 ☐		—
Pulse voltage if applicable (kV)					-		—
Supplementary information: Between Live part and accessible part							
Distance 3:	R	> 3.0	3.0	11.1A	> 5.0	5.0	11.1B
Working voltage (V)					240 V		—
PTI					< 600 ☐ ≥ 600 ☐		—
Pulse voltage if applicable (kV)					-		—
Supplementary information: Between Live part and mounting surface							

** Insulation type: B – Basic; S – Supplementary; R – Reinforced. See also IEC 60598-1 Annex M.

4.7 (11.2)	TABLE II: Creepage distances and clearances						N/A
Minimum distances (mm) for a.c. higher than 30 kHz sinusoidal voltages							
Applicable part of IEC 61347-1 Table 7 and 8* or IEC 60664-4 Table 1 and 2							
Distances	Insulation type **	Measured clearance	Required		Measured creepage	Required	
			clearance	*Table		creepage	*Table
Distance 1:							
Working voltage (V)							—
Frequency if applicable (kHz)							—
PTI					< 600 ☐ ≥ 600 ☐		—

IEC 60598-2-4							
Clause	Requirement + Test				Result - Remark		Verdict
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV)							—
Supplementary information:							
Distance 2:							
Working voltage (V)							—
Frequency if applicable (kHz)							—
PTI					< 600 ☐ ≥ 600 ☐		—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV)							—
Supplementary information:							
Distance 3:							
Working voltage (V)							—
Frequency if applicable (kHz)							—
PTI					< 600 ☐ ≥ 600 ☐		—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV)							—
Supplementary information: ** Insulation type: B – Basic; S – Supplementary; R – Reinforced. See also IEC 60598-1 Annex M.							

4.15a (13.2.1) TABLE: Ball Pressure Test of Thermoplastics				P
Allowed impression diameter (mm)			≤2	—
Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)	
Plastic enclosure	See Annex 1	75	0.5	
Supplementary information:				

4.15b (13.3.1) TABLE: Needle-flame test (IEC 60695-11-5)					N/A
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

Supplementary information:

4.15c (13.3.2)	TABLE: Glow-wire test (IEC 60695-2-11)				P
Glow wire temperature		650			—
Object/ Part No./ Material	Manufacturer/ trademark		Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
Plastic enclosure	See Annex 1		No	0	pass

Supplementary information:

4.15d (13.4)	TABLE: Proof tracking test (IEC 60112)					N/A
Test voltage PTI :			175 V			—
Object/ Part No./ Material		Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens			Verdict
Supplementary information:						

Supplementary information:

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 1		TABLE: Critical components information					P
Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾	
Internal wire	B	CIXI SHUANGHONG WIRE CO LTD	1332	20 AWG, 300 V, 200 °C	IEC 60598-1 IEC 60598-2-4	Tested with appliance UL E333296	
plastic enclosure	C	Quanzhou Ruiling Arts and Crafts Co., Ltd.	HI-121H	ABS	IEC 60598-1 IEC 60598-2-4	Tested with appliance	
LED chips	C	Shenzhen Yiguangtong Optoelectronics Co., Ltd	LS R976-NR- 1	VF: 2.5V IF: 20mA CCT: 1000K	IEC 62031 IEC/TR 62778	Tested with appliance	
Supplementary information: ¹⁾ Provided evidence ensures the agreed level of compliance. See OD-CB2039. The codes above have the following meaning: A - The component is replaceable with another one, also certified, with equivalent characteristics B - The component is replaceable if authorised by the test house C - Integrated component tested together with the appliance D - Alternative component							

IEC 60598-2-4							
Clause	Requirement + Test	Result - Remark	Verdict				
ANNEX 2	TABLE: Temperature measurements, thermal tests of Section 12		P				
	Type reference :	9711AFWY	—				
	Lamp used :	LEDs	—				
	Lamp control gear used..... :	-	—				
	Mounting position of luminaire..... :	Normal mounting	—				
	Supply wattage (W) :	30 W	—				
	Supply current (A)..... :	-	—				
	Temperatures in test 1 - 4 below are corrected for ta (°C) :	25 °C	—				
	- abnormal operating mode :	-	—				
4.12 (12.4)	- test 1: rated voltage :	-	—				
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage :	1.06×240 V	—				
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage :	-	—				
	Through wiring or looping-in wiring loaded by a current of A during the test :	-	—				
4.12 (12.5)	Through wiring or looping-in wiring loaded by a current of A during the test :	-	—				
Temperature measurements, (°C)							
Part	Ambient	Clause 12.4 – normal				Clause 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
Plastic enclosure	25	-	52.5	-	Cl.13.2.1	-	-
Internal wire	25	-	42.8	-	90	-	-
Mounting surface	25	-	40.7	-	90	-	-
Supply cord	25	-	27.4	-	90	-	-
Supplementary information:							

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
ANNEX 3	Screw terminals (part of the luminaire)		N/A
(14)	SCREW TERMINALS		N/A
(14.2)	Type of terminal		—
	Rated current (A)		—
(14.3.2.1)	One or more conductors		N/A
(14.3.2.2)	Special preparation		N/A
(14.3.2.3)	Terminal size		N/A
	Cross-sectional area (mm ²)		—
(14.3.3)	Conductor space (mm)		N/A
(14.4)	Mechanical tests		
(14.4.1)	Minimum distance		N/A
(14.4.2)	Cannot slip out		N/A
(14.4.3)	Special preparation		N/A
(14.4.4)	Nominal diameter of thread (metric ISO thread)	M	N/A
	External wiring		N/A
	No soft metal		N/A
(14.4.5)	Corrosion		N/A
(14.4.6)	Nominal diameter of thread (mm)		N/A
	Torque (Nm)		N/A
(14.4.7)	Between metal surfaces		N/A
	Lug terminal		N/A
	Mantle terminal		N/A
	Pull test; pull (N)		N/A
(14.4.8)	Without undue damage		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
ANNEX 4	Screwless terminals (part of the luminaire)		N/A
(15)	SCREWLESS TERMINALS		N/A
(15.2)	Type of terminal		—
	Rated current (A)		—
(15.3.1)	Material		N/A
(15.3.2)	Clamping		N/A
(15.3.3)	Stop		N/A
(15.3.4)	Unprepared conductors		N/A
(15.3.5)	Pressure on insulating material		N/A
(15.3.6)	Clear connection method		N/A
(15.3.7)	Clamping independently		N/A
(15.3.8)	Fixed in position		N/A
(15.3.10)	Conductor size		N/A
	Type of conductor		N/A
(15.5)	Terminals and connections for internal wiring		N/A
(15.5.1)	Mechanical tests		N/A
(15.5.1.1.1)	Pull test spring-type terminals (4 N, 4 samples)		N/A
(15.5.1.1.2)	Pull test pin or tab terminals (4 N, 4 samples)		N/A
	Insertion force not exceeding 50 N		N/A
(15.5.1.2)	Permanent connections: pull-off test (20 N)		N/A
(15.5.2)	Electrical tests		
	Voltage drop (mV) after 1 h (4 samples)		N/A
	Voltage drop of two inseparable joints		N/A
	Number of cycles:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples)		N/A
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples)		N/A
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples)		N/A
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples)		N/A
(15.6)	Terminals and connections for external wiring		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
(15.6.1)	Conductors		N/A
	Terminal size and rating		N/A
15.6.2	Mechanical tests		N/A
(15.6.2.1)	Pull test spring-type terminals or welded connections (4 samples); pull (N)		N/A
(15.6.2.2)	Pull test pin or tab terminals (4 samples); pull (N)		N/A
(15.6.3)	Electrical tests		N/A
	Tests according 15.6.3.1 + 15.6.3.2 in IEC 60598-1		N/A

(15.6.3.1) (15.6.3.2)	TABLE: Contact resistance test / Heating tests										N/A
	Voltage drop (mV) after 1 h										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop of two inseparable joints										
	Voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV) :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop after 50th alt. 100th cycle										
	Max. allowed voltage drop (mV) :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV) :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 50th alt. 100th cycle										

IEC 60598-2-4										
Clause	Requirement + Test					Result - Remark				Verdict
	Max. allowed voltage drop (mV) :									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										
Supplementary information:										

Attachment No.1**IEC60598_2_4D ATTACHMENT**

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

ATTACHMENT TO TEST REPORT IEC 60598-2-4 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES Luminaires Part 2: Particular requirements Section 4: Portable general purpose luminaires			
Differences according to EN 60598-2-4:1997 used in conjunction with EN 60598-1:2015			
Annex Form No. EU_GD_IEC60598_2_4D			
Annex Form Originator OVE			
Master Annex Form 2017-11-10			
Copyright © 2017 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			

	CENELEC COMMON MODIFICATIONS (EN)		P
--	--	--	----------

4.5 (3)	MARKING		P
4.5 (3.3.101)	For luminaires not supplied with terminal block: Adequate warning on the package		N/A

4.6 (4)	CONSTRUCTION		N/A
4.6 (4.11.6)	Electro-mechanical contact systems		N/A


4.10 (5)	EXTERNAL AND INTERNAL WIRING		P
4.10 (5.2.1)	Connecting leads		N/A
	- without a means for connection to the supply		N/A
	- terminal block specified		N/A
	- relevant information provided		N/A
	- compliance with 4.6, 4.7.1, 4.7.2, 4.10.1, 11.2, 12 and 13.2 of Part 1		N/A
4.10 (5.2.2)	Cables equal to EN 50525		P
	Replace table 5.1 – Supply cord		P

4.12 (12)	ENDURANCE TESTS AND THERMAL TESTS		P
4.12 (12.4.2c)	Thermal test (normal operation) see footnote c to table 12.2 relating to unsleeved fixed wiring		P

Attachment No.2

IEC 62031

Clause	Requirement + Test	Result - Remark	Verdict
13 (14)	FAULT CONDITIONS		P
- (14.1)	In compliance with IEC 61347-1 (clause numbers between parentheses refer to IEC 61347-1)		N/A
	When operated under fault conditions the LED module:		N/A
	- does not emit flames or molten material		N/A
	- does not produce flammable gases		N/A
	- protection against accidental contact not impaired		N/A
	Thermally protected controlgear does not exceed the marked temperature value		N/A
	Fault conditions: capacitors, resistors or inductors without proof of compliance with relevant specifications have been short-circuited or disconnected		N/A
- (14.2)	Short-circuit of creepage distances and clearances if less than specified in clause 16 in Part 1 (except between live parts and accessible metal parts)		N/A
	Creepage distances on printed boards less than specified in clause 16 in Part 1 provided with coating according to IEC 60664-3		N/A
- (14.3)	Short-circuit or interruption of semiconductor devices		N/A
- (14.4)	Short-circuit across insulation consisting of lacquer, enamel or textile		N/A
- (14.5)	Short-circuit across electrolytic capacitors		N/A
- (14.6)	After the tests has been carried out on three samples:		N/A
	The insulation resistance $\geq 1 \text{ M}\Omega$		N/A
	No flammable gases		N/A
	No accessible parts have become live		N/A
	During the tests, a five-layer tissue paper, where the test specimen is wrapped, does not ignite		N/A
- (14.7)	Relevant fault condition tests with high-power supply		N/A
13.2	Overpower condition		P
	Module withstands overpower condition >15 min.		P
	Module with automatic protective device or power limiter, test performed 15 min. at limit.		N/A
	No fire, smoke or flammable gas is produced		P
	Molten material does not ignite tissue paper, spread below the module		P

Attachment No.3**Product Photos**Details of: Fig. 1Details of: Fig. 2

Attachment No.3

Product Photos

Details of: Fig. 3



- End of test report -