



TEST REPORT
IEC 60598-2-17
Luminaires
Part 2: Particular requirements
Section 17: Luminaires for stage lighting, television and
film studios (outdoor and indoor)

Report Number. : AOC251112008S

Date of issue : 2025-11-25

Total number of pages : 41 pages

Name of Testing Laboratory preparing the Report : Shenzhen AOCE Electronic Technology Service Co., Ltd
Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China

Applicant's name : TEAMADE INDUSTRIAL CO., LIMITED

Address : RM18, 27/F, HO KING COMM CTR, 2-16 FAYUEN
ST,MONGKOK ,KOWLOON, HONG KONG

Test specification:

Standard : ☒ IEC 60598-2-17:2017
☒ IEC 60598-1:2020

Test procedure : Type testing

Non-standard test method : N/A

Test Report Form No. : IEC60598_2_17E

Test Report Form(s) Originator : Intertek Semko AB

Master TRF : Dated 2017-08

Copyright © 2017 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.

General disclaimer:

The test results presented in this report relate only to the object tested.


This report shall not be reproduced, except in full, without the written approval of the Issuing Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the Testing Laboratory, responsible for this Test Report.

Test item description	HSS SPEEDLITE FLASH LIGHT	
Trade Mark	JINBEI	
Manufacturer	TEAMADE INDUSTRIAL CO., LIMITED RM18, 27/F, HO KING COMM CTR, 2-16 FAYUEN ST,MONGKOK ,KOWLOON, HONG KONG	
Model/Type reference.....	HD 2PLUS	
Ratings.....	DC 5V, 3A, Class III, IP20, ta:25°C	
Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):		
☒	Testing Laboratory:	Shenzhen AOCE Electronic Technology Service Co., Ltd
Testing location/ address		Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China
Tested by (name, function, signature)		ZhiCong Xian Technical Engineer <i>ZhiCong Xian</i>
Approved by (name, function, signature) ..		murry.yu Technical Manager <i>Robin. Yu</i>
Testing procedure: CTF Stage 1:		
☐	N/A	
Testing location/ address		
Tested by (name, function, signature)		
Approved by (name, function, signature) ..		
Testing procedure: CTF Stage 2:		
☐	N/A	
Testing location/ address		
Tested by (name + signature).....		
Witnessed by (name, function, signature) . :		
Approved by (name, function, signature) .. :		
Testing procedure: CTF Stage 3:		
☐	N/A	
Testing procedure: CTF Stage 4:		
☐	N/A	
Testing location/ address		
Tested by (name, function, signature)		
Witnessed by (name, function, signature) . :		
Approved by (name, function, signature) .. :		
Supervised by (name, function, signature) :		

List of Attachments (including a total number of pages in each attachment): Attachment No.1: Photo document.	
Summary of testing:	
Tests performed (name of test and test clause): - All testing were performed on model HD 2PLUS - IEC 60598-2-17:2018 - IEC 60598-1:2021+A11:2022	Testing location: Shenzhen AOCE Electronic Technology Service Co., Ltd Room 202, 2nd Floor, No.12th Building of Xinhe Tongfuyu Industrial Park, Fuhai Street, Baoan District, Shenzhen, Guangdong, China
Summary of compliance with National Differences (List of countries addressed): None	

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.

**Remark:**

The mark as above is the requirements required by the safety standard. For the final production, the additional marks which do not give rise to misunderstanding may be added.

Test item particulars..... :	
Classification of installation and use..... : Fixed luminaire	
Supply Connection : Battery	
Possible test case verdicts:	
- test case does not apply to the test object..... : N/A	
- test object does meet the requirement..... : P (Pass)	
- test object does not meet the requirement..... : F (Fail)	
Testing..... :	
Date of receipt of test item : 2025-10-27	
Date (s) of performance of tests : 2025-10-27 to 2025-11-25	
General remarks:	
"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a ☐ comma / ☐ point is used as the decimal separator. Clause numbers between brackets refer to clauses in IEC 60598-1	
Manufacturer's Declaration per sub-clause 4.2.5 of IEC 02:	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided :	☐ Yes ☒ Not applicable
When differences exist; they shall be identified in the General product information section.	
Name and address of factory (ies) : SHANGHAI JINBEI PHOTOGRAPHIC EQUIPMENTS CO., LTD. 7H BLOCK, NO.788 DINGXI ROAD, 200052 SHANGHAI,P.R.CHINA	

General product information:

/

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.4 (0)	GENERAL TEST REQUIREMENTS		
17.4 (0.1)	Information for luminaire design considered.....:	Yes ☒ No ☐ Lamp standard:	—
17.4 (0.3)	More sections applicable	Yes ☒ No ☐ Section/s:	—

17.5 (2)	CLASSIFICATION		—
17.5 (2.2)	Type of protection	Class III	P
17.5 (2.3)	Degree of protection	IP20	P
17.5 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces.....:	Yes ☒ No ☐	—
17.5 (2.5)	Luminaire for normal use	Yes ☒ No ☐	—
	Luminaire for rough service	Yes ☐ No ☒	—

17.6 (3)	MARKING		—
17.6 (3.2)	Mandatory markings		P
	Position of the marking		P
	Format of symbols/text		P
17.6 (3.3)	Additional information		P
	Language of instructions		P
17.6 (3.3.1)	Combination luminaires		N/A
17.6 (3.3.2)	Nominal frequency in Hz		N/A
17.6 (3.3.3)	Operating temperature		N/A
17.6 (3.3.4)	Symbol or warning notice		N/A
17.6 (3.3.5)	Wiring diagram		N/A
17.6 (3.3.6)	Special conditions		N/A
17.6 (3.3.7)	Metal halide lamp luminaire – warning		N/A
17.6 (3.3.8)	Limitation for semi-luminaires		N/A
17.6 (3.3.9)	Power factor and supply current		P
17.6 (3.3.10)	Suitability for use indoors		P
17.6 (3.3.11)	Luminaires with remote control		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.6 (3.3.12)	Clip-mounted luminaire – warning		N/A
17.6 (3.3.13)	Specifications of protective shields		N/A
17.6 (3.3.14)	Symbol for nature of supply		P
17.6 (3.3.15)	Rated current of socket outlet		N/A
17.6 (3.3.16)	Rough service luminaire		N/A
17.6 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments		N/A
17.6 (3.3.18)	Non-ordinary luminaires with PVC cable		N/A
17.6 (3.3.19)	Protective conductor current in instruction if applicable		N/A
17.6 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		N/A
17.6 (3.3.21)	Non replaceable and non-user replaceable light sources information provided		N/A
	Cautionary symbol		N/A
17.6 (3.3.22)	Controllable luminaires, classification of insulation provided		P
17.6 (3.4)	Test with water		P
	Test with hexane		P
	Legible after test		P
	Label attached		P
17.6.1 (-)	If luminaire design imposes restriction of use the luminaire is marked with		P
	a) Indication of the “top”		N/A
	b) Designed position or range of angle		N/A
	c) Mounting arrangements		N/A
17.6.2 (-)	Warnings if replaceable light sources		N/A
17.6.3 (-)	Maximum ambient temperature t_a		N/A
17.6.4 (-)	Minimum distances from flammable materials		N/A
17.6.5 (-)	Warning against opening immediately if applicable		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.6.6 (-)	Highest exterior surface temperature if exceeds 70 °C		N/A
17.6.7 (-)	Instruction leaflet contain warnings		N/A
	a) Visibly damaged shields shall be changed		N/A
	b) Damaged or thermally deformed lamp shall be changed		N/A
	c) Only intended for professional use		N/A

17.7 (4)	CONSTRUCTION		N/A
17.7 (4.2)	Components replaceable without difficulty		N/A
17.7 (4.3)	Wireways smooth and free from sharp edges		N/A
17.7 (4.4)	Lampholders		N/A
17.7 (4.4.1)	Integral lampholder		N/A
17.7 (4.4.2)	Wiring connection		N/A
17.7 (4.4.3)	Lampholder for end-to-end mounting		N/A
17.7 (4.4.4)	Positioning		N/A
	- pressure test (N)		N/A
	After test the lampholder comply with relevant standard sheets and show no damage		N/A
	After test on single-capped lampholder the lampholder have not moved from its position and show no permanent deformation		N/A
	- bending test (N)		N/A
	After test the lampholder have not moved from its position and show no permanent deformation		N/A
17.7 (4.4.5)	Peak pulse voltage		N/A
17.7 (4.4.6)	Centre contact		N/A
17.7 (4.4.7)	Parts in rough service luminaires resistant to tracking		N/A
17.7 (4.4.8)	Lamp connectors		N/A
17.7 (4.4.9)	Caps and bases correctly used		N/A
17.7 (4.4.10)	Light source for lampholder or connection according IEC 60061 not connected another way		N/A
17.7 (4.5)	Starter holders		N/A
	Starter holder in luminaires other than class II		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
	Starter holder class II construction		N/A
17.7 (4.6)	Terminal blocks		N/A
	Tails		N/A
	Unsecured blocks		N/A
17.7 (4.7)	Terminals and supply connections		N/A
17.7 (4.7.1)	Contact to metal parts		N/A
17.7 (4.7.2)	Test 8 mm live conductor		N/A
	Test 8 mm earth conductor		N/A
17.7 (4.7.3)	Terminals for supply conductors		N/A
17.7 (4.7.3.1)	Welded method and material		N/A
	- stranded or solid conductor		N/A
	- spot welding		N/A
	- welding between wires		N/A
	- Type Z attachment		N/A
	- mechanical test according to 15.6.2		N/A
	- electrical test according to 15.6.3		N/A
	- heat test according to 15.6.2.3 and 15.6.2.4		N/A
17.7 (4.7.4)	Terminals other than supply connection		N/A
17.7 (4.7.5)	Heat-resistant wiring/sleeves		N/A
17.7 (4.7.6)	Multi-pole plug		N/A
	- test at 30 N		N/A
17.7 (4.8)	Switches		N/A
	- adequate rating		N/A
	- adequate fixing		N/A
	- polarized supply		N/A
	- compliance with IEC 61058-1 for electronic switches		N/A
17.7 (4.9)	Insulating lining and sleeves		N/A
17.7 (4.9.1)	Retainment		N/A
	Method of fixing		N/A
17.7 (4.9.2)	Insulated linings and sleeves:		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
	Resistant to a temperature > 20 °C to the wire temperature or		N/A
	a) & c) Insulation resistance and electric strength		N/A
	b) Ageing test. Temperature (°C):		N/A
17.7 (4.10)	Double or reinforced insulation		N/A
17.7 (4.10.1)	No contact, mounting surface – accessible metal parts – wiring of basic insulation		N/A
	Safe installation fixed luminaires		N/A
	Capacitors and switches		N/A
	Interference suppression capacitors according to IEC 60384-14		N/A
17.7 (4.10.2)	Assembly gaps:		N/A
	- not coincidental		N/A
	- no straight access with test probe		N/A
17.7 (4.10.3)	Retainment of insulation:		N/A
	- fixed		N/A
	- unable to be replaced; luminaire inoperative		N/A
	- sleeves retained in position		N/A
	- lining in lampholder		N/A
17.7 (4.10.4)	Protective impedance device		N/A
	Double or reinforced insulation bridged by appropriate and at least two resistors or two Y2 capacitors or one Y1 capacitor		N/A
	Y1 or Y2 capacitors comply with IEC 60384-14		N/A
	Resistors comply with test (a) in 14.1 of IEC 60065		N/A
17.7 (4.11)	Electrical connections and current-carrying parts		P
17.7 (4.11.1)	Contact pressure		P
17.7 (4.11.2)	Screws:		N/A
	- self-tapping screws		N/A
	- thread-cutting screws		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.7 (4.11.3)	Screw locking:		N/A
	- spring washer		N/A
	- rivets		N/A
17.7 (4.11.4)	Material of current-carrying parts		P
17.7 (4.11.5)	No contact to wood or mounting surface		P
17.7 (4.11.6)	Electro-mechanical contact systems		N/A
17.7 (4.12)	Screws and connections (mechanical) and glands		P
17.7 (4.12.1)	Screws not made of soft metal		P
	Screws of insulating material		P
	Torque test: torque (Nm); part		P
	Torque test: torque (Nm); part		P
	Torque test: torque (Nm); part		N/A
17.7 (4.12.2)	Screws with diameter < 3 mm screwed into metal		N/A
17.7 (4.12.4)	Locked connections:		N/A
	- fixed arms; torque (Nm)		N/A
	- lampholder; torque (Nm)		
	- push-button switches; torque 0,8 Nm		N/A
17.7 (4.12.5)	Screwed glands; force (Nm)		N/A
17.7 (4.13)	Mechanical strength		P
17.7 (4.13.1)	Impact tests:		P
	- fragile parts; energy (Nm)		N/A
	- other parts; energy (Nm)		P
	1) live parts		P
	2) linings		N/A
	3) protection		P
	4) covers		P

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.7 (4.13.3)	Straight test finger		N/A
17.7 (4.13.4)	Rough service luminaires		N/A
	- IP54 or higher		N/A
	a) fixed		N/A
	b) hand-held		N/A
	c) delivered with a stand		N/A
	d) for temporary installations and suitable for mounting on a stand		N/A
17.7 (4.13.6)	Tumbling barrel		N/A
17.7 (4.14)	Suspensions, fixings and means of adjusting		N/A
17.7 (4.14.1)	Mechanical load:		N/A
	A) four times the weight		N/A
	B) torque 2,5 Nm		N/A
	C) bracket arm; bending moment (Nm)		N/A
	D) load track-mounted luminaires		N/A
	E) clip-mounted luminaires, glass-shelve. Thickness (mm)		N/A
	Metal rod. diameter (mm)		N/A
	Fixed luminaire or independent control gear without fixing devices		N/A
17.7 (4.14.2)	Load to flexible cables		N/A
	Mass (kg)		—
	Stress in conductors (N/mm ²)		N/A
	Mass (kg) of semi-luminaire		N/A
	Bending moment (Nm) of semi-luminaire		N/A
17.7 (4.14.3)	Adjusting devices:		N/A
	- flexing test; number of cycles		N/A
	- strands broken		N/A
	- electric strength test afterwards		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.7 (4.14.4)	Telescopic tubes: cords not fixed to tube; no strain on conductors		N/A
17.7 (4.14.5)	Guide pulleys		N/A
17.7 (4.14.6)	Strain on socket-outlets		N/A
17.7 (4.15)	Flammable materials		P
	- glow-wire test 650°C.....:	See Test Table 17.16 (13.3.2)	P
	- spacing ≥ 30 mm		N/A
	- screen withstanding test of 13.3.1		N/A
	- screen dimensions		N/A
	- no fiercely burning material		P
	- thermal protection		N/A
	- electronic circuits exempted		N/A
17.7 (4.15.2)	Luminaires made of thermoplastic material with lamp control gear		N/A
	a) construction		N/A
	b) temperature sensing control		N/A
	c) surface temperature		N/A
17.7 (4.16)	Luminaires for mounting on normally flammable surfaces		P
	No lamp control gear	(compliance with Section 12)	P
17.7 (4.16.1)	Lamp control gear spacing:		N/A
	- spacing 35 mm		N/A
	- spacing 10 mm		N/A
17.7 (4.16.2)	Thermal protection:		N/A
	- in lamp control gear		N/A
	- external		N/A
	- fixed position		N/A
	- temperature marked lamp control gear		N/A
17.7 (4.16.3)	Design to satisfy the test of 12.6	(see clause 12.6)	N/A
17.7 (4.17)	Drain holes		N/A
	Clearance at least 5 mm		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.7 (4.18)	Resistance to corrosion		N/A
17.7 (4.18.1)	- rust-resistance		N/A
17.7 (4.18.2)	- season cracking in copper		N/A
17.7 (4.18.3)	- corrosion of aluminium		N/A
17.7 (4.19)	Ignitors compatible with ballast		N/A
17.7 (4.20)	Rough service vibration		N/A
17.7 (4.21)	Protective shield		N/A
17.7 (4.21.1)	Shield fitted if tungsten halogen lamps or metal halide lamps		N/A
	Shield of glass if tungsten halogen lamps		N/A
17.7 (4.21.2)	Particles from a shattering lamp not impair safety		N/A
17.7 (4.21.3)	No direct path		N/A
17.7 (4.21.4)	Impact test on shield		N/A
	Glow-wire test on lamp compartment	See Test Table 17.16 (13.3.2)	N/A
17.7 (4.22)	Attachments to lamps not cause overheating or damage		N/A
17.7 (4.23)	Semi-luminaires comply Class II		N/A
17.7 (4.24)	Photobiological hazards		N/A
17.7 (4.24.1)	No excessive UV radiation if tungsten halogen lamps and metal halide lamps (Annex P)		N/A
17.7 (4.24.2)	Retinal blue light hazard		N/A
	Luminaires with E_{thr} :		N/A
	a) Fixed luminaires		N/A
	- distance x m, borderline between RG1 and RG2....:		N/A
	- marking and instruction according 3.2.23		N/A
	b) Portable and handheld luminaires		N/A
	- marking according 3.2.23 if RG1 exceeded at 200 mm according to IEC/TR 62778		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
	Portable luminaires for children IEC 60598-2-10 and Mains socket outlet nightlights IEC 60598-2-12 not exceed RG1 at 200 mm according to IEC/62778		N/A
17.7 (4.25)	Mechanical hazard		P
	No sharp point or edges		P
17.7 (4.26)	Short-circuit protection		N/A
17.7 (4.26.1)	Adequate means of uninsulated accessible SELV parts		N/A
17.7 (4.26.2)	Short-circuit test with test chain according 4.26.3		N/A
	Test chain not melt through		N/A
	Test sample not exceed values of Table 12.1 and 12.2		N/A
17.7 (4.27)	Terminal blocks with integrated screwless earthing contacts		N/A
	Test according Annex V		N/A
	Pull test of terminal fixing (20 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Pull test of mechanical connection (50 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Voltage drop test, resistance < 0,05 Ω		N/A
17.7 (4.28)	Fixing of thermal sensing control		N/A
	Not plug-in or easily replaceable type		N/A
	Reliably kept in position		N/A
	No adhesive fixing if UV radiations from a lamp can degrade the fixing		N/A
	Not outside the luminaire enclosure		N/A
	Test of adhesive fixing:		N/A
	Max. temperature on adhesive material (°C).....:		—
	100 cycles between t min and t max		N/A
	Temperature sensing control still in position		N/A
17.7 (4.29)	Luminaires with non-replaceable light source		N/A
	Not possible to replace light source		N/A
	Live part not accessible after parts have been opened by hand or tools		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.7 (4.30)	Luminaires with non-user replaceable light source		N/A
	If protective cover provide protection against electric shock and marked with “caution, electric shock risk” symbol:		N/A
	Minimum two fixing means		N/A
17.7 (4.31)	Insulation between circuits		N/A
	Circuits insulated from LV supply fulfil requirements according 4.31.1 – 4.31.3		N/A
	Controllable luminaires requiring same level of insulation for all components, the insulation between control terminals and LV supply fulfil requirements according 4.31.1 – 4.31.3		N/A
17.7 (4.31.1)	SELV circuits		N/A
	Used SELV source		N/A
	Voltage $\leq$ ELV		N/A
	Insulating of SELV circuits from LV supply		N/A
	Insulating of SELV circuits from other non SELV circuits		N/A
	Insulating of SELV circuits from FELV		N/A
	Insulating of SELV circuits from other SELV circuits		N/A
	SELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Plugs and socket-outlets does not have protective conductor contact		N/A
17.7 (4.31.2)	FELV circuits		N/A
	Used FELV source		N/A
	Voltage $\leq$ ELV		N/A
	Insulating of FELV circuits from LV supply		N/A
	FELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to enter socket-outlets of other voltage systems		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
	Socket outlets does not admit plugs of other voltage systems		N/A
	Socket-outlets does not have protective conductor contact		N/A
17.7 (4.31.3)	Other circuits		N/A
	Other circuits insulated from accessible parts according Table X.1		N/A
	Class II construction with equipotential bonding for protection against indirect contacts with live parts:		N/A
	- conductive parts are connected together		N/A
	- test according 7.2.3		
	- conductive part not cause an electric shock in case of an insulation fault		N/A
	- equipotential bonding in master/slave applications		N/A
	- master luminaire provided with terminal for accessible conductive parts of slave luminaires		N/A
	- slave luminaire constructed as class I		N/A
17.7 (4.32)	Overvoltage protective devices		N/A
	Comply with IEC 61643-11		N/A
	External to controlgear and connected to earth:		N/A
	- only in fixed luminaires		N/A
	- only connected to protective earth		N/A
17.7.1 (-)	Not possible to insert a lamp into a "live" lampholder if applicable		N/A
17.7.2 (-)	Prevent immediate access to the lamp or marked according 17.6.5 if applicable		N/A
17.7.3 (-)	Retain particles of glass or quartz produced in the event of the lamp shattering if glass bulb lamp		N/A
	Comply with test 4.21.4 in IEC 60598-1 with 0,5 Nm		N/A
17.7.4 (-)	Bearing parts of hanger are capable to support six time the weight of the luminaire		N/A
	Non-combustible materials		N/A
	Parts of hanger carrying a proportion of the weight of the luminaire are capable to support six time the proportion of weight		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
	Connection between hanger and luminaire locked		N/A
	Test 1 h with six times the weight of the luminaire		N/A
17.7.5 (-)	Removable accessories cannot fall out of the luminaire from any position		N/A
17.7.6 (-)	If applicable a secondary suspension provided and passed the test		N/A

17.8 (11)	CREEPAGE DISTANCES AND CLEARANCES		N/A
17.8 (11.2)	Creepage distances and clearances	See Table 17.8 (11.2)	
	Impulse withstand category (Normal category II) (Category III Annex U, table U.1)	Category II ☐ Category III ☐	—

17.9 (7)	PROVISION FOR EARTHING		N/A
17.9 (7.2.1 + 7.2.3)	Accessible metal parts		N/A
	Metal parts in contact with supporting surface		N/A
	Resistance < 0,5 Ω		N/A
	Self-tapping screws used		N/A
	Thread-forming screws		N/A
	Thread-forming screw used in a groove		N/A
	Earth makes contact first		N/A
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
	Protective earthing of the luminaire not via built-in control gear		N/A
17.9 (7.2.2 + 7.2.3)	Earth continuity in joints, etc.		N/A
17.9 (7.2.4)	Locking of clamping means		N/A
	Compliance with 4.7.3		N/A
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
17.9 (7.2.5)	Earth terminal integral part of connector socket		N/A
17.9 (7.2.6)	Earth terminal adjacent to mains terminals		N/A
17.9 (7.2.7)	Electrolytic corrosion of the earth terminal		N/A
17.9 (7.2.8)	Material of earth terminal		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
	Contact surface bare metal		N/A
17.9 (7.2.10)	Class II luminaire for looping-in		N/A
	Double or reinforced insulation to functional earth		N/A
17.9 (7.2.11)	Earthing core coloured green-yellow		N/A
	Length of earth conductor		N/A

17.10 (14)	SCREW TERMINALS		N/A
	Separately approved; component list		N/A
	Part of the luminaire		N/A

17.10 (15)	SCREWLESS TERMINALS AND ELECTRICAL CONNECTIONS		N/A
	Separately approved; component list	(see Annex 1)	N/A
	Part of the luminaire.....	(see Annex 4)	N/A

17.11 (5)	EXTERNAL AND INTERNAL WIRING		P
17.11 (5.2)	Supply connection and external wiring		P
17.11 (5.2.1)	Means of connection.....		P
	Outdoor luminaire has not PVC insulated external wiring if not class III or SELV ≤ 25 V a.c./60 V d.c. or protected from outdoor environment		N/A
17.11 (5.2.2)	Type of cable		N/A
	Nominal cross-sectional area (mm ²).....		N/A
	Cables equal to IEC 60227 or IEC 60245		N/A
17.11 (5.2.3)	Type of attachment, X, Y or Z		N/A
17.11 (5.2.5)	Type Z not connected to screws		N/A
17.11 (5.2.6)	Cable entries:		N/A
	- suitable for introduction		N/A
	- adequate degree of protection		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.11 (5.2.7)	Cable entries through rigid material have rounded edges		N/A
17.11 (5.2.8)	Insulating bushings:		N/A
	- suitably fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- tubes or guards made of insulating material		N/A
17.11 (5.2.9)	Locking of screwed bushings		N/A
17.11 (5.2.10)	Cord anchorage:		N/A
	- covering protected from abrasion		N/A
	- clear how to be effective		N/A
	- no mechanical or thermal stress		N/A
	- no tying of cables into knots etc.		N/A
	- insulating material or lining		N/A
17.11 (5.2.10.1)	Cord anchorage for type X attachment:		N/A
	a) at least one part fixed		N/A
	b) types of cable		N/A
	c) no damaging of the cable		N/A
	d) whole cable can be mounted		N/A
	e) no touching of clamping screws		N/A
	f) metal screw not directly on cable		N/A
	g) replacement without special tool		N/A
	Glands not used as anchorage		N/A
	Labyrinth type anchorages		N/A
17.11 (5.2.10.2)	Adequate cord anchorage for type Y and type Z attachment		N/A
17.11 (5.2.10.3)	Tests:		N/A
	- impossible to push cable; unsafe		N/A
	- pull test: 25 times; pull (N)		N/A
	- torque test: torque (Nm)		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
	- displacement ≤ 2 mm		N/A
	- no movement of conductors		N/A
	- no damage of cable or cord		N/A
	- function independent of electrical connection		N/A
17.11 (5.2.11)	External wiring passing into luminaire		N/A
17.11 (5.2.12)	Looping-in terminals		N/A
17.11 (5.2.13)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		N/A
17.11 (5.2.14)	Mains plug same protection		N/A
	Class III luminaire plug		N/A
	No unsafe compatibility		N/A
17.11 (5.2.16)	Appliance inlets (IEC 60320)		N/A
	Installation couplers (IEC 61535)		N/A
	Other appliance inlet or connector according relevant IEC standard		N/A
17.11 (5.2.17)	No standardized interconnecting cables properly assembled		N/A
17.11 (5.2.18)	Used plug in accordance with		N/A
	- IEC 60083		N/A
	- other standard		N/A
17.11 (5.3)	Internal wiring		P
17.11 (5.3.1)	Internal wiring of suitable size and type		P
	Through wiring		N/A
	- not delivered/ mounting instruction		N/A
	- factory assembled		N/A
	- socket outlet loaded (A).....:		N/A
	- temperatures: (see Annex 2)		N/A
	Green-yellow for earth only		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.11 (5.3.1.1)	Internal wiring connected directly to fixed wiring		N/A
	Cross-sectional area (mm ²)		N/A
	Insulation thickness		N/A
	Extra insulation added where necessary		N/A
17.11 (5.3.1.2)	Internal wiring connected to fixed wiring via internal current-limiting device		N/A
	Adequate cross-sectional area and insulation thickness		N/A
17.11 (5.3.1.3)	Double or reinforced insulation for class II		N/A
17.11 (5.3.1.4)	Conductors without insulation		N/A
17.11 (5.3.1.5)	SELV current-carrying parts		P
17.11 (5.3.1.6)	Insulation thickness other than PVC or rubber		N/A
17.11 (5.3.2)	Sharp edges etc.		P
	No moving parts of switches etc.		N/A
	Joints, raising/lowering devices		N/A
	Telescopic tubes etc.		N/A
	No twisting over 360°		P
17.11 (5.3.3)	Insulating bushings:		N/A
	- suitable fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- cables with protective sheath		N/A
17.11 (5.3.4)	Joints and junctions effectively insulated		N/A
17.11 (5.3.5)	Strain on internal wiring		N/A
17.11 (5.3.6)	Wire carriers		N/A
17.11 (5.3.7)	Wire ends not tinned		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
	Wire ends tinned: no cold flow		N/A
17.11.1 (-)	Cross-sectional area - current (A) : - area (mm ²) :		N/A
17.11.2 (-)	Plugs and sockets not interchangeable		N/A

17.12 (8)	PROTECTION AGAINST ELECTRIC SHOCK		-
17.12 (8.2.1)	Live parts not accessible		P
	Basic insulated parts not used on the outer surface without appropriate protection		P
	Basic insulated parts not accessible with standard test finger on portable, settable and adjustable luminaires		P
	Basic insulated parts not accessible with Ø 50 mm probe from outside, other types of luminaires		N/A
	Lamp and starterholders in portable and adjustable luminaires comply with double or reinforced insulation requirements		N/A
	Basic insulation only accessible under lamp or starter replacement		N/A
	Protection in any position		P
	Double-ended tungsten filament lamp		N/A
	Insulation lacquer not reliable		N/A
	Double-ended high pressure discharge lamp		N/A
	Relevant warning according to 3.2.18 fitted to the luminaire		N/A
17.12 (8.2.2)	Portable luminaire adjusted in most unfavourable position		N/A
17.12 (8.2.3.a)	Class II luminaire:		N/A
	- basic insulated metal parts not accessible during starter or lamp replacement		N/A
	- basic insulation not accessible other than during starter or lamp replacement		N/A
	- glass protective shields not used as supplementary insulation		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.12 (8.2.3.b)	BC lampholder of metal in class I luminaires shall be earthed		N/A
17.12 (8.2.3.c)	SELV circuits with exposed current carrying parts:		P
	Ordinary luminaire:		N/A
	- voltage under load (V)		N/A
	- no-load voltage (V)		N/A
	- touch current if applicable (mA)		N/A
	One conductive part insulated if required		N/A
	Other than ordinary luminaire:		N/A
	- nominal voltage		N/A
	Class III luminaire only for connection to SELV		N/A
	Class III luminaire not provided with means for protective earthing		N/A
17.12 (8.2.4)	Portable luminaire have protection independent of supporting surface		N/A
17.12 (8.2.5)	Compliance with the standard test finger or relevant probe		N/A
17.12 (8.2.6)	Covers reliably secured		N/A
17.12 (8.2.7)	Luminaire other than below with capacitor > 0,5 μ F not exceed 50 V 1 min after disconnection		N/A
	Portable luminaire with capacitor > 0,1 μ F (0.25) not exceed 34 V 1 s after disconnection		N/A
	Other luminaires with capacitor > 0,1 μ F (0.25) with plug and track adaptors not exceed 60 V 5 s after disconnection		N/A

17.13 (12)	ENDURANCE TEST AND THERMAL TEST	—
17.13 (12.3)	Endurance test:	—
	- mounting-position	—
	- test temperature (°C)	—
	- total duration (h)	—
	- supply voltage: Un factor; calculated voltage (V) ...:	—
	- lamp used	—

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.13 (12.3.2)	After endurance test:		—
	- no part unserviceable		P
	- luminaire not unsafe		P
	- no damage to track system		N/A
	- marking legible		P
	- no cracks, deformation etc.		P
17.13 (12.4)	Thermal test (normal operation)	(see Annex 2)	P
17.13 (12.5)	Thermal test (abnormal operation)	(see Annex 2)	P
17.13 (12.6)	Thermal test (failed lamp control gear condition):		P
17.13 (12.6.1)	Through wiring or looping-in wiring loaded by a current of (A)		—
	- case of abnormal conditions.....		—
	- electronic lamp control gear		N/A
	- measured winding temperature (°C): at 1,1 Un		—
	- measured mounting surface temperature (°C) at 1,1 Un		N/A
	- calculated mounting surface temperature (°C)		N/A
	- track-mounted luminaires		N/A
17.13 (12.6.2)	Temperature sensing control		N/A
	- case of abnormal conditions.....		—
	- thermal link		N/A
	- manual reset cut-out		N/A
	- auto reset cut-out		N/A
	- measured mounting surface temperature (°C)		N/A
	- track-mounted luminaires		N/A
17.13 (12.7)	Thermal test (failed lamp control gear in plastic luminaires):		N/A
17.13 (12.7.1)	Luminaire without temperature sensing control		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.13 (12.7.1.1)	Luminaire with fluorescent lamp $\leq 70W$		N/A
	Test method 12.7.1.1 or Annex W		—
	Test according to 12.7.1.1:		N/A
	- case of abnormal conditions.....		—
	- Ballast failure at supply voltage (V)		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
	Test according to Annex W:		N/A
	- case of abnormal conditions.....		—
	- measured winding temperature ($^{\circ}C$): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part ($^{\circ}C$): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part ($^{\circ}C$).....		—
	Ball-pressure test.....	See Table 17.16 (13.2.1)	N/A
17.13 (12.7.1.2)	Luminaire with discharge lamp, fluorescent lamp $> 70W$, transformer $> 10 VA$		N/A
	- case of abnormal conditions.....		—
	- measured winding temperature ($^{\circ}C$): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part ($^{\circ}C$): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part ($^{\circ}C$).....		—
	Ball-pressure test.....	See Table 17.16 (13.2.1)	N/A
17.13 (12.7.1.3)	Luminaire with short circuit proof transformers $\leq 10 VA$		N/A
	- case of abnormal conditions.....		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
17.13 (12.7.2)	Luminaire with temperature sensing control		N/A
	- thermal link	Yes ☐ No ☐	—
	- manual reset cut-out.....	Yes ☐ No ☐	—

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
	- auto reset cut-out.....:	Yes ☐ No ☐	—
	- case of abnormal conditions.....:		—
	- highest measured temperature of fixing point/ exposed part (°C):.....:		—
	Ball-pressure test:	See Table 17.16 (13.2.1)	P
17.13.1 (-)	If IP > IP 20 relevant test of (12.4), (12.5), (12.6) and (12.7) after (9.2) before (9.3) specified in 17.14		—
17.13.2 (-)	Exterior surface temperature	(see Annex 2)	P

17.14 (9)	RESISTANCE TO DUST AND MOISTURE		P
17.14 (-)	If IP > IP 20 the order of tests as specified in clause 17.13		—
17.14 (9.2)	Tests for ingress of dust, solid objects and moisture:		
	- classification according to IP	IP20	P
	- mounting position during test		P
	- fixing screws tightened; torque (Nm)		—
	- tests according to clauses		—
	- electric strength test afterwards		P
	a) no deposit in dust-proof luminaire		N/A
	b) no talcum in dust-tight luminaire		N/A
	c) no trace of water on current-carrying parts or on insulation where it could become a hazard		N/A
	c.1) For luminaires without drain holes – no water entry		N/A
	c.2) For luminaires with drain holes – no hazardous water entry		N/A
	d) no water in watertight or pressure watertight luminaire		N/A
	e) no contact with live parts (IP 2X)		P
	e) no entry into enclosure (IP 3X and IP 4X)		N/A
	e) no contact with live parts through drain holes and ventilation slots (IP3X and IP4X)		N/A
	f) no trace of water on part of lamp requiring protection from splashing water		N/A
	g) no damage of protective shield or glass envelope		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
17.14 (9.3)	Humidity test 48 h	Relative humidity 93%, temperature 25°C	P

17.15 (10)	INSULATION RESISTANCE AND ELECTRIC STRENGTH		P
17.15 (10.2.1)	Insulation resistance test		P
	Cable or cord covered by metal foil or replaced by a metal rod of mm Ø		—
	Insulation resistance (MΩ)		—
	SELV		--
	- between current-carrying parts of different polarity :	>100 MΩ	P
	- between current-carrying parts and mounting surface	>100 MΩ	P
	- between current-carrying parts and metal parts of the luminaire	>100 MΩ	P
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts		N/A
	- Insulation bushings as described in Section 5		N/A
	Other than SELV		--
	- between live parts of different polarity		N/A
	- between live parts and mounting surface		N/A
	- between live parts and metal parts		N/A
	- between live parts of different polarity through action of a switch		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts		N/A
	- Insulation bushings as described in Section 5		N/A
17.15 (10.2.2)	Electric strength test		P
	Dummy lamp		N/A
	Luminaires with ignitors after 24 h test		N/A
	Luminaires with manual ignitors		N/A
	Test voltage (V)		P
	SELV		--

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
	- between current-carrying parts of different polarity :	500 V	P
	- between current-carrying parts and mounting surface	500 V	P
	- between current-carrying parts and metal parts of the luminaire	500 V	P
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts		N/A
	- Insulation bushings as described in Section 5		N/A
	Other than SELV		N/A
	- between live parts of different polarity		N/A
	- between live parts and mounting surface.....		N/A
	- between live parts and metal parts.....		N/A
	- between live parts of different polarity through action of a switch		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts		N/A
	- Insulation bushings as described in Section 5		N/A
17.15 (10.3)	Touch current or protective conductor current (mA):		N/A

17.16 (13)	RESISTANCE TO HEAT, FIRE AND TRACKING		-
17.16 (13.2.1)	Ball-pressure test.....	See Test Table 17.16 (13.2.1)	P
17.16 (13.3.1)	Needle-flame test (10 s)	See Test Table 17.16 (13.3.1)	P
17.16 (13.3.2)	Glow-wire test (650°C).....	See Test Table 17.16 (13.3.2)	P
17.16 (13.4)	Proof tracking test (IEC 60112)	See Test Table 17.16 (13.4)	N/A

IEC 60598-2-17							
Clause	Requirement + Test				Result - Remark		Verdict
17.8 (11.2)	TABLE: Creepage distances and clearances						P
	Minimum distances (mm) for a.c. (50/60 Hz) sinusoidal voltages						P
	Applicable part of IEC 60598-1 Table 11.1* and 11.2*						P
	Insulation type **	Measured clearance	Required		Measured creepage	Required	
			clearance	*Table		creepage	*Table
Distance 1:	-	-	-	-	-	-	-
Working voltage (V)					DC 5V (No request)		—
PTI					< 600 ☒ ≥ 600 ☐		—
Pulse voltage if applicable (kV)					-		—
Supplementary information:							
Distance 2:	-	-	-	-	-	-	-
Working voltage (V)							—
PTI					< 600 ☒ ≥ 600 ☐		—
Pulse voltage if applicable (kV)					-		—
Supplementary information:							
Distance 3:	-	-	-	-	-	-	-
Working voltage (V)							—
PTI					< 600 ☒ ≥ 600 ☐		—
Pulse voltage if applicable (kV)					-		—
Supplementary information:							

** Insulation type: B – Basic; S – Supplementary; R – Reinforced. See also IEC 60598-1 Annex M.

IEC 60598-2-17				
Clause	Requirement + Test		Result - Remark	Verdict
17.16 (13.2.1)	TABLE: Ball Pressure Test of Thermoplastics			
Allowed impression diameter (mm) :				—
Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)	
LED cover	-	75	0.9	
Plastic eN/Aclosure	-	75	0.9	
LED PCB	-	125	0.6	
Supplementary information:				

17.16 (13.3.1)	TABLE: Needle-flame test (IEC 60695-11-5)				
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
LED PCB	-	10	No	0	pass
Supplementary information:					

17.16 (13.3.2)	TABLE: Glow-wire test (IEC 60695-2-11)				
Glow wire temperature :				650°C	—
Object/ Part No./ Material	Manufacturer/ trademark		Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
LED cover	-		No	0	pass
Plastic eN/Aclosure	-		No	0	pass
Any flame or glowing of the sample extinguished within 30 s of withdrawing the glow-wire, and any burning or molten drop did not ignite the underlying parts (Yes/No)					
Supplementary information:					

IEC 60598-2-17						
Clause	Requirement + Test			Result - Remark		Verdict
17.16 (13.4)	TABLE: Proof tracking test (IEC 60112)					
Test voltage PTI :			175 V			—
Object/ Part No./ Material		Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens			Verdict
Supplementary information:						

ANNEX 1		TABLE: Critical components information					P
Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾	
Battery	C	JINBEI	HD Mini	7.4V, 3200mAh	IEC 60598-1	CE	
-LED chips	C	CREE	Cree 3030	Vf: 3.7V, If: 350mA, CCT: max. 6500K	IEC 62031	Tested with appliance	
LED PCB	C	HUN/AG HIN/AG ELECTRON/AIC S CO LTD	HH-01	V-0, 130 °C	IEC 60598-1	UL E327405 Tested with appliance	
LED cover	C	A SCHULMAN/A CUSTOM COMPOUN/ADIN /AG N/AE IN/AC	PC(x)M3FRU L	V-0, 80 °C	IEC 60598-1	UL E343939 Tested with appliance	
Supplementary information:							
¹⁾ Provided evidence ensures the agreed level of compliance. See OD-CB2039. The codes above have the following meaning: A - The component is replaceable with another one, also certified, with equivalent characteristics B - The component is replaceable if authorised by the test house C - Integrated component tested together with the appliance D - Alternative component							

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 2	TABLE: Temperature measurements, thermal tests of Section 12		P				
	Type reference.....:	HD 2PLUS	—				
	Lamp used	LED	—				
	Lamp control gear used	/	—				
	Mounting position of luminaire	Normal mounting	—				
	Supply wattage (W)	-	—				
	Supply current (A).....:	-	—				
	Calculated power factor	25°C	—				
	Table: measured temperatures corrected for ta = 25 °C:						
	- abnormal operating mode		—				
	- test 1: rated voltage		—				
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage	5V×1.06	—				
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage		—				
	- test 4: 1,1 times rated voltage or 1,05 times rated wattage		—				
	Through wiring or looping-in wiring loaded by a current of A during the test		—				
Temperature measurements, (°C)							
Part	Ambient	Clause 12.4 – normal				Clause 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
LED PCB	25	-	98.4	-	130	-	-
LED cover	25	-	76.0	-	cl.13.2	-	-
Plastic enclosure	25	-	29.1	-	cl.13.2		
Mounting surface	25	-	30.6	-	90	-	-
Supplementary information:							

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
ANNEX 3	Screw terminals (part of the luminaire)		N/A
(14)	SCREW TERMINALS		N/A
(14.2)	Type of terminal		—
	Rated current (A)		—
(14.3.2.1)	One or more conductors		N/A
(14.3.2.2)	Special preparation		N/A
(14.3.2.3)	Terminal size		N/A
	Cross-sectional area (mm ²)		—
(14.3.3)	Conductor space (mm)		N/A
(14.4)	Mechanical tests		N/A
(14.4.1)	Minimum distance		N/A
(14.4.2)	Cannot slip out		N/A
(14.4.3)	Special preparation		N/A
(14.4.4)	Nominal diameter of thread (metric ISO thread)	M	N/A
	External wiring		N/A
	No soft metal		N/A
(14.4.5)	Corrosion		N/A
(14.4.6)	Nominal diameter of thread (mm)		N/A
	Torque (Nm)		N/A
(14.4.7)	Between metal surfaces		N/A
	Lug terminal		N/A
	Mantle terminal		N/A
	Pull test; pull (N)		N/A
(14.4.8)	Without undue damage		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
ANNEX 4	Screwless terminals (part of the luminaire)		N/A
(15)	SCREWLESS TERMINALS		N/A
(15.2)	Type of terminal		—
	Rated current (A)		—
(15.3.1)	Material		N/A
(15.3.2)	Clamping		N/A
(15.3.3)	Stop		N/A
(15.3.4)	Unprepared conductors		N/A
(15.3.5)	Pressure on insulating material		N/A
(15.3.6)	Clear connection method		N/A
(15.3.7)	Clamping independently		N/A
(15.3.8)	Fixed in position		N/A
(15.3.10)	Conductor size		N/A
	Type of conductor		N/A
(15.5)	Terminals and connections for internal wiring		N/A
(15.5.1)	Mechanical tests		N/A
(15.5.1.1.1)	Pull test spring-type terminals (4 N, 4 samples)		N/A
(15.5.1.1.2)	Pull test pin or tab terminals (4 N, 4 samples)		N/A
	Insertion force not exceeding 50 N		N/A
(15.5.1.2)	Permanent connections: pull-off test (20 N)		N/A
(15.5.2)	Electrical tests		N/A
	Voltage drop (mV) after 1 h (4 samples)		N/A
	Voltage drop of two inseparable joints		N/A
	Number of cycles:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples)		N/A
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples)		N/A
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples)		N/A
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples)		N/A
(15.6)	Terminals and connections for external wiring		N/A

IEC 60598-2-17			
Clause	Requirement + Test	Result - Remark	Verdict
(15.6.1)	Conductors		N/A
	Terminal size and rating		N/A
15.6.2	Mechanical tests		N/A
(15.6.2.1)	Pull test spring-type terminals or welded connections (4 samples); pull (N)		N/A
(15.6.2.2)	Pull test pin or tab terminals (4 samples); pull (N)		N/A
(15.6.3)	Electrical tests		N/A
	Tests according 15.6.3.1 + 15.6.3.2 in IEC 60598-1		N/A

(15.6.3.1) (15.6.3.2)	TABLE: Contact resistance test / Heating tests										N/A
	Voltage drop (mV) after 1 h										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop of two inseparable joints										
	Voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV) :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop after 50th alt. 100th cycle										
	Max. allowed voltage drop (mV) :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV) :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 50th alt. 100th cycle										

IEC 60598-2-17										
Clause	Requirement + Test					Result - Remark				Verdict
	Max. allowed voltage drop (mV) :									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										
Supplementary information:										

Attachment No.1


Product Photos

Details of: Fig. 1



Details of: Fig. 2



Attachment No.1**Product Photos**Details of: Fig. 3Details of: Fig. 4

Attachment No.1

Product Photos

Details of: Fig. 5



Details of: Fig. 6



----- End of test report -----